

Specifications*

MODEL		SB22m	SB25h	SB31m	SB31h
ENGINE (DIESEL)					
Model		A1000N2	A1100N2	A1100T2	
Type		Water cooled 3-cylinder diesel			
Displacement (cc)		1058	1175		
Engine gross power (HP/ kW)		21/ 15.3	24/ 17.9	30/ 23.2	30/ 23.2
Rated speed (rpm.)		2600			
Fuel tank capacity (l.)		23			
Combustion system		Indirect			
Battery (V.)		12			
Air cleaner		Dry, element			
TRAVELLING SYSTEM					
Transmission		Mechanical	Hydrostatic	Mechanical	Hydrostatic
Groups		6 F / 2 R	2	6 F / 2 R	2
Max. forward speed (km/h)		21.9	21.4	24.6	
Drive system		4 wheel drive			
Clutch		Dry, single plate			
Brake		Wet, multidisc			
Sperddifferential		Rear			
TIRES					
Agri	Front	6-12	6-12	7-16	7-16
	Rear	9.5-16	9.5-16	11.2-20	11.2-20
Turf	Front	23x8.5x12	23x8.5x12	23x8.5x12	23x8.5x12
	Rear	33x12.5-16.5	33x12.5-16.5	33x12.5-16.5	33x12.5-16.5
Industry	Front	23x8.5x12	23x8.5x12	23x8.5x12	23x8.5x12
	Rear	12-16.5	12-16.5	12-16.5	12-16.5
PTO					
Rear PTO (rpm.)		540 and 960			
Mid PTO (rpm.)		2600			
HYDRAULISCH SYSTEEM					
Main (lpm.)		18.2			
Steering (lpm.)		13			
Steering category		Power Assisted Hydrostatic			
Control type		Position			
Remote control valve		1 double acting rear			
Hitch category		Cat. 1			
Max. lift capacity (kg)		650			
DIMENSIONS					
Length (mm)		3066		3122	
Width (mm)		1124		1369	
Height (mm)		2216		2330	
Min. turning radius (mm)		4600		5200	
Ground clearance (mm)		315		407	
Wheelbase (mm)		1502		1670	
Weight incl. ROPS (kg)		770	780	885	908

*The specifications are subject to change without notice.

Important information

• Improper use of any product may cause serious or fatal injury. Read, understand and follow carefully the operating and safety instructions in your owner's manual before using such products.



SHIBAURA EUROPE BV

Begonialaan 7

NL - 6851 TE Huissen

T. 0031 (0)26 326 9999

F. 0031 (0)26 326 9990

E. info@shibaura.com

I. www.shibaura.com

Dealer: