

SHIBAURA

PRICE LIST 11-2020



- * Subcompact tractor
- * Compact tractors
- * Tractors
- * Frontmowers

- * Reelmower
- * Fairway mower
- * Mower with collector
- * Rough terrain-/ slopemower



Shibaura Europe BV
Begonialaan 7
NL - 6851 TE Huissen
The Netherlands
T. 0031 26326 9999
F. 0031 26326 9990
E. info@shibaura.com
www.shibaura.com

SHIBAURA EUROPE BV

Begonialaan 7
NL - 6851 TE Huissen
the Netherlands

Phone 0031 26 326 9999
Fax 0031 26 326 9990
Mobile 0031 621883620 (Rob de Dreu)
0031 629544770 (Wendy Franken)
0031 621534773 (Fanny Franken)
0031 654314001 (Paul Franken)

Website : www.shibaura.com
E-mail : info@shibaura.com

Chamber of Commerce Arnhem 10036098
VAT. no. NL009486938B01

Rabobank no. 12.40.42.775
Swiftcode: RABONL2U
IBAN: NL92 RABO 0124 0427 75

		<i>Phone:</i>	<i>E-mail:</i>
Sales Benelux	Rob de Dreu	0031 621883620	robdedreu@shibaura.com
Sales/ Spareparts	Hans Broekstra	0031 26 3269991	broekstra@shibaura.com
Technical Service	Patrick Janssen	0031 26 3269994	garantie@shibaura.com
Technical Service	Erik Derksen	0031 26 3269994	td@shibaura.com
Managing Director	Fanny Franken	0031 26 3269993	fannyfranken@shibaura.com
Managing Director	Wendy Franken	0031 26 3269997	wendyfranken@shibaura.com
Managing Director	Paul Franken	0031 26 3269995	franken@shibaura.com

Shibaura Deutschland GmbH		Carl-Hans-Straße 4	D-51674 Wiehl
Phone/ Fax		0049 2296 999010	0049 2296 9990111
Sales Germany	Martin Potthoff	0049 151 72725303	potthoff@shibaura.de
Sales Germany	Kai Meschke	0049 2296 9990115	meschke@shibaura.de

**With this price list all previous price lists are expired.
All prices are in EURO excl. VAT.
All deliveries according to Fedecom terms and conditions 2014.**

CONTENTS:

	PAGE:
SUBCOMPACT TRACTOR SHIBAURA SX25.....	2
COMPACTTRACTOR SHIBAURA SB22m.....	6
COMPACTTRACTOR SHIBAURA SB25h.....	7
COMPACTTRACTOR SHIBAURA SB36h/SB36hc.....	10
COMPACTTRACTOR SHIBAURA SB47h/SB47hc.....	11
TRACTOR SHIBAURA SB62h/SB62hc.....	14
TRACTOR SHIBAURA SB78mc.....	16
FRONTMOWER SHIBAURA CM214.....	19
FRONTMOWERS SHIBAURA CM254.....	21
REELMOWER SHIBAURA SR370.....	25
FAIRWAY MOWER SHIBAURA SR888.....	26
ROUGH TERRAIN-/ SLOPE MOWER SHIBAURA SG280.....	28
MOWERS WITH COLLECTOR SHIBAURA SX20G/ SX26G/ SX26D.....	29
ROTARYMOWERSFORTRACTORS.....	31
FLAILMOWERS, SALTSREADERSFORTRACTORS.....	31

- Prices and technical details are subject to change without previous notice.

- PTO rotation direction mentions the rotation with your face towards the end of the shaft.

SHIBAURA SUBCOMPACTTRACTOR SX25

FOUR WHEEL DRIVE

ENGINE 3 cylinder, low noise, watercooled diesel engine, **STAGE V**
21.2 kW / 26.0 hp (SAE) 18.3 kW / 24.5 hp DIN, 1131 cc

TORQUE 67.0 Nm/ 2400 rpm.

TRANSMISSION Hydrost. / 2 groups: forwards : 0-17 km/h
backwards : 0-11.2 km/h

REAR PTO Independent: rear 540 rpm., mid 2200 rpm.
direction of rotation clockwise

3-POINT LINKAGE Cat. 1 with lifting capacity 715 kg

HYDR. CAPACITY 24.6 liters/ min., ≈ 130 bar

TURNING RADIUS 254 cm

TREAD front: 1164 mm rear: 1270 mm

GROUND CLEARANCE 185 mm

FUEL TANK CAPACITY 26 liters

FLOOR Flat floor without handles

LENGTH 244.5 cm

WIDTH 118 cm

HEIGHT 228 cm

WEIGHT with ROB 696 kg

<i>Code:</i>	<i>Description:</i>	<i>Euro:</i>
SX25	SX25 (incl. tires as desired)	13,990,-

Choice tires:

- WTT SX25	Wide turf-tires	F: 18x8.5-10	R: 26x12.00-12
- TERRA SX25	Terra/ industrial tires	F: 18x8.5-10	R: 26x12.00-12

Additional net price tires, speed about 20 km/h (midmower/ frontloader not possible):

- INDSX25	Big wide agri tires	F: 23x8,5-12	R: 10,0/75-15,3	650,-
- HSAGRSX25	Big small agri tires	F: 6-12	R: 180/95-16	990,-
- BWTT SX25	Big wide turf tires	F: 27x10,5-15	R: 22x9,5-12	990,-

Min. outer diameter pro tire type:

- turf tires	: 118 cm
- industrial/ terra tires	: 119 cm
- big, wide agri tires	: 118 cm
- big, small agri tires	: 109 cm
- big, wide turf tires	: 119 cm



ACCESSORIES SHIBAURA SX25

<i>Code:</i>	<i>Description:</i>	<i>Euro:</i>
	SHIBAURA MIDMOUNTED MOWER	
SXM54	Midmounted mower, working width 1.37 m, side discharge	2,800,-
SXM60	Midmounted, working width 1.50 m, side discharge	2,990,-
1317045	Indep. liftkit for midmounted mower (VENT necessary)	520,-
VENT	Valve block	490,-
ST.2003	Mulchset 1.37 m	670,-
ST.2001	Mulchset 1.50 m	670,-
	PAULI FRONTLIFT	
PA-115SH	Frontlift with quick coupling and 2 liftcylinders	1,490,-
PA-120SH	Front PTO, 2000 rpm. (only with PA-115SH)	1,050,-
PA-122SH	Hydraulic set, 2 valves, 4 hydr. connections 2F en 2R	1,050,-
	Mounting (net)	190,-
	Mounting frontlift with big tires (net)	250,-
340003281/60441	Double acting valve with two quick coupling rear	710,-
	Mounting (net)	120,-
	SHIBAURA FRONTLOADER incl. bucket 1.17 m (not with cabin)	
FL26	Frontloader with double acting liftcylinder and hydraulic operation of the bucket	3,690,-
PAL-FL26	Pallet fork	800,-
	Mounting (netto)	250,-
KS322	MAUSER CABIN	5,350,-
	safetyglass, electr. windscreen wiper with sprayer, heating, removable and lockable doors, led-working lights outside mirror, sunblind, height 2,00 m	
	Mounting (net)	350,-
ZLAMP	Flashing light	50,-
	Mounting (net)	30,-
	MATEV GRASSCOLLECTOR (340003281/60441 or PA-122SH necessary)	
1317127	Grasscollector CS-G650, 650 litres	5,490,-
1317129	Grasscollector CS-H650, 650 l. with hydraulic hightipping	6,990,-
1317003	Duo airtyres 260x85 (recommended option)	670,-
1317026	Midmower connection with pipe for midmower	840,-
1317026	Frontmower connection with pipe for frontmower	870,-
	MORGNIEUX GRASSCOLLECTOR	
Turbo530LD	Grasscollector 530LD, 530 litres with manual opening	3,950,-
Turbo530HD	Grasscollector 530HD, 530 litres with hydraulic hightipping	5,650,-
	(340003281/60441 or PA-122SH necessary)	
V04A80	Pair of wheels (recommended)	740,-
V04A82	Road lights	230,-
V04A85	Full container buzzer	230,-

ACCESSORIES SHIBAURA SX25

<i>Code:</i>	<i>Description:</i>	<i>Euro:</i>
34030040	SNOWBLADE incl. hydr. side adjustment incl. plastic scraping rib 1.40 x 0.50 m	1,900,-
PA-4200K	SNOWBLADE 1.40 m. with lift (short construction) incl. hydr. valve with joystick	3,990,-
MATEV SWEEPER		
1317693	Sweeper 1.40 x Ø 0.45 m incl. hydr. side adjustment	3,990,-
KEHR3	Extra price design with 3 sweeperspeeds	130,-
1317716	Dustcollector	780,-
1317705	Side brush mechanical driven	790,-
1317724	Dustprotector	280,-
CERRUTI SNOWBLOWER		
BASICL1200	Working width 1.20 m, 2000 rpm, incl. side adjustment	6,290,-
OTHER		
PA-129.1SH	Towing-hook rear	660,-
999999004	Frontweight 27 kg (max. 3 pieces) per piece	75,-
STEUNSX	Bracket for mounting frontweight	60,-
Z622.735	Drawbar cat. 1	75,-
HEFBOK	Lift triangle with towing ball	130,-
PA-134.1SH	HST Autopedal	160,-
FARMSL	Air suspension seat	1,030,-
E41W0889	Cruise Control	830,-



SPECIFICATIONS SHIBAURA SX25

MODEL		SX25
ENGINE (DIESEL)		
Model		S773L-EU
Type		Water cooled, 3-cylinder diesel, STAGE V
Displacement	(cc)	1131
Engine gross power	(DIN HP / kW)	24.5 / 18.3
Torque	(Nm)	67.0 @ 2400
Rated speed	(rpm.)	3000
Fuel tank capacity	(l.)	26
TRAVELLING SYSTEM		
Transmission		HST
Groups		F/R 2
Travelling speed	Forwards	(km/h) 0 - 17.0
	Reverse	(km/h) 0 - 11.5
Differential lock		mechanically switchable
Brake		wet disc type
TIRES		
Industry	Front	18x8,50-10
	Rear	26x12,00-12
Turf	Front	18x8,50-10
	Rear	26x12,00-12
PTO independent		
Power	(HP)	20.5
Rear	(rpm.)	540
Mid	(rpm.)	2000
Front		option
HYDRAULIC SYSTEM		
Pump capacity	(lpm/ bar)	24.6/ 130
Steering category		Hydraulic Power Steering
Remote control valve		option: 1 x double acting rear
3-point hitch		Cat. I
Maximum lifting capacity	(kg)	715
DIMENSIONS		
Length	(mm)	2445
Width	(mm)	1180
Height	(mm)	2280
Ground clearance / Wheelbase	(mm)	185 / 1400
Weight	(kg)	696

SHIBAURA COMPACTTRACTOR SB22m

FOUR WHEEL DRIVE ENGINE

3 cylinder, watercooled diesel engine, **STAGE V**
15.3 kW / 21 hp, 1058 cc

TORQUE

61,8 Nm @ 1900 rpm

TRANSMISSION

Mechanical; 6 F, 2 R, max. speed 19,0 km/h

REAR PTO

540 and 1000 rpm., direction of rotation clockwise

MID PTO

2600 rpm., direction of rotation clockwise

3-POINT LINKAGE

Cat. 1 with lifting capacity 650 kg

HYDR. CAPACITY

Main 18.2 liters/ min., steering 13 liters/min., 137 bar

STEERING

Power steering hydraulic

GROUND CLEARANCE

315 mm

FUEL TANK CAPACITY

23 liters

STANDARD

Weight carrier with 6 frontweights of 20 kg

LENGTH

3066 mm (with frontweights)

WIDTH agri

1124 mm

HEIGHT agri

2216 mm

WEIGHT agri

812 kg

Code:

SB22M-AG

Description:

SB22m Agri tires

F: 6.00-12

R:9.5-16

Euro:

11,950,-

Additional net price tires:

- TTSB22

Turf tires

F: 23-8.5-12

R: 33x12.5-16.5

700,-

- INDSB22

Industrial tires

F: 23-8.5-12

R: 12-16.5

700,-

Min. outer diameter pro tire type:

- agri tires : 112 cm

- turf tires : 133 cm

- industrial tires : 132 cm



SHIBAURA COMPACTTRACTOR SB25h

FOUR WHEEL DRIVE ENGINE

3 cylinder, watercooled diesel engine, **STAGE V**
17.9 kW / 24 hp, 1175 cc

TORQUE

75.6 Nm @ 2000 rpm

TRANSMISSION

Hydrostatic; 2 groups, max. speed 21.4 km/h

REAR PTO

540 and 1000 rpm., direction of rotation clockwise

MID PTO

2600 rpm., direction of rotation clockwise

3-POINT LINKAGE

Cat. 1 with lifting capacity 650 kg

HYDR. CAPACITY

Main 18.2 liters/ min., steering 13 liters/min., 137 bar

POWER STEERING

Standard

GROUND CLEARANCE

315 mm

FUEL TANK CAPACITY

23 liters

STANDARD

Weight carrier with 6 frontweights of 20 kg

LENGTH

3066 mm (with frontweights)

WIDTH agri

1124 mm

HEIGHT agri

2216 mm

WEIGHT agri

830 kg

Code:

SB25H-AG

Description:

SB25h Agri tires

F: 6.00-12

R:9.5-16

Euro:

13,550,-

Additional net price tires:

- TTSB22

Turf tires

F: 23x8.5-12

R: 33x12.5-16.5

700,-

- INDSB22

Industrial tires

F: 23x8.5-12

R: 12-16.5

700,-

Min. outer diameter pro tire type:

- agri tires : 112 cm

- turf tires : 133 cm

- industrial tires : 132 cm



ACCESSORIES SB22/ SB25

<i>Code:</i>	<i>Description:</i>	<i>Euro:</i>
BM60	SHIBAURA MIDMOUNTED MOWER Midmounted mower, working width 1,50 m	2,980,-
	PAULI FRONTLIFT	
PA-3100B	Frontlift with quick coupling Cat. 0	1,490,-
PA-3105B	Front PTO, 2000 rpm, clockwise (only with PA-3100B)	1,380,-
PA-3106B	Hydraulic set, 2 valves, 4 hydr. connections 2 F and 2 lift Mounting (net)	1,250,- 290,-
	SHIBAURA FRONTLOADER	
BL00SL	Frontloader SB 22/ 25 incl. bucket 121 cm (not with cabin) Mounting (net)	3,950,- 305,-
42120/42221	Pallet fork 100 cm, pin-coupling	1,040,-
8102-600	Option third function	470,-
42326	Bale spike	470,-
	CABIN	
42180	Cabin SB22/ 25 with heating, height 198 cm Mounting (net)	5,490,- 390,-
	OTHERS	
42111	Mudguardset front SB22/ 25 with agri tires	190,-
42112	Mudguardset front SB22/ 25 with turf/ industrial tires	190,-
42162	Support for trailer hitchcoupling W180	700,-
42163	Adjustable trailer hitchcoupling W180 (only with 42162)	420,-
42164	Towing ball coupling W180	400,-
42160	Hitchcoupling (attached to top link)	460,-



SPECIFICATIONS SHIBAURA SB22 / SB25

MODEL		SB22m	SB25h
ENGINE (DIESEL)			
Model		A1000N2	A1100N2
Type		Water cooled 3-cyl. diesel STAGE V	
Displacement (cc)		1058	1175
Engine gross power (HP/ kW)		21 / 15.3	24 / 17.9
Torque (Nm)		61.8 @ 1900	75.6 @ 2000
Rated speed (rpm.)		2600	
Fuel tank capacity (l.)		23	
Air cleaner		Dry, element	
TRAVELLING SYSTEM			
Transmission		Mechanical	Hydrostatic
Groups		6 F / 2 R	2
Max. forward speed (km/h)		19	21.4
Drive system		4 wheel drive	
Clutch / Brake		Dry, single plate / Wet multidisc	
Sperddifferential		Rear	
TIRES			
Agri	Front	6-12	6-12
	Rear	9.5-16	9.5-16
Turf	Front	23x8.5x12	23x8.5x12
	Rear	33x12.5-16.5	33x12.5-16.5
Industry	Front	23x8.5x12	23x8.5x12
	Rear	12-16.5	12-16.5
PTO			
Rear PTO (rpm.)		540 and 1000	
Mid PTO (rpm.)		2600	
HYDRAULIC SYSTEM			
Main (lpm./ bar)		18.2/ 137	
Steering (lpm.)		13	
Steering category		Power Assisted Hydrostatic	
Control type		Position	
Remote control valve		2 double acting rear	
Hitch category/ max. lift capacity (kg)		Cat. 1/ 650	
DIMENSIONS (agri tires)			
Length x Width x Height (mm)		3066 x 1124 x 2216	
Wheelbase/ ground clearance (mm)		1502/ 315	
Weight incl. ROPS (kg)		812	830

SHIBAURA COMPACTTRACTOR SB36h / SB36hc

FOUR WHEEL DRIVE

ENGINE

3 cylinder, watercooled diesel engine

25.7 kW / 35 hp, 1714 cc

TORQUE

110 Nm @ 1650 rpm

TRANSMISSION

Hydrostatic, 3 groups, max. speed 29.2 km/h

REAR PTO

Independent 540 and 750 rpm., headland management, direction of rotation clockwise

3-POINT LINKAGE

Cat. 1 with lifting capacity 1650 kg

HYDR. CAPACITY

Main 33.6 liters/ min., steering 18 liters/min., 180 bar

POWER STEERING

Standard

GROUND CLEARANCE

335 mm

FUEL TANK CAPACITY

27 liters

CABIN

SB36hc with factory cabin incl. heating, air conditioning, radio and led-working lights front and rear

LxWxH rops/ agri

3096 x 1451 x 2643 mm

WEIGHT

SB36h: 1383 kg **SB36hc**: 1563 kg

- Clear dashboard and adjustable steering wheel
- Ergonomically placed cross lever for operating 2 dw valves.
- 2 dw valves at the rear, 1 with latch (cabin)
- 1 dw valve rear (without cabin)
- Auto-Throttle (combined accelerator / accelerator pedal)
- Cruise Control
- Rear PTO equipped with headland management system
- Traction control on the rear lift
- Rear towbar
- Weight carrier with 6 frontweights of 17 kg

Code:

Description:

Euro:

SB36H-AG	SB36h Agri tires STAGE V	F: 8-16	R: 12.4-24	21,400,-
SB36HC-AG	SB36hc Agri tires	F: 7-16	R: 11.2-24	23,900,-
SB36HC-AG	SB36hc Agri-tires STAGE V	F: 7-16	R: 11.2-24	27,600,-

Additional net price tires:

- TTSB36	Turf tires	F: 27x8.5-15	R: 41x14-20	950,-
- INDSB36H	Industrial tires	F: 10-16.5	R: 420/70-24	1,600,-
- INDSB36HC	Industrial tires cabin	F: 25x8.5-14	R: 380/70R19.5	1,400,-
- GALSB36	Galaxy garden pro	F: 260/70R16	R: 380/70R24	1,990,-

Min. outer diameter pro tire type:

- agri tires : 145 cm (narrowest 135 cm)
- agri tires with cabin : 132 cm
- turf tires : 164 cm
- industrial tires : 153 cm
- galaxy garden pro : 151 cm



SHIBAURA COMPACTTRACTOR SB47h / SB47hc

FOUR WHEEL DRIVE ENGINE

3 cylinder, watercooled diesel engine
33.5 kW / 45.5 hp 1714 cc

TORQUE

145 Nm @ 1900 rpm

TRANSMISSION

Hydrostatic, 3 groups, max. speed 29.2 km/h

REAR PTO

Independent 540 and 750 rpm., headland management, direction of rotation clockwise

3-POINT LINKAGE

Cat. 1 with lifting capacity 1650 kg

HYDR. CAPACITY

Main 33.6 liters/ min., steering 18 liters/min., 180 bar

POWER STEERING

Standard

GROUND CLEARANCE

335 mm

FUEL TANK CAPACITY

27 liters

CABIN

SB47hc with factory cabin incl. heating, air conditioning, radio and led-workinglights front and rear

LxWxH

rops/ agri 3096 x 1451 x 2643 mm

WEIGHT

agri **SB47h:** 1423 kg **SB47hc:** 1563 kg

- Clear dashboard and adjustable steering wheel
- Ergonomically placed cross lever for operating 2 dw valves.
- 2 dw valves at the rear, 1 with latch (cabin)
- 1 dw valve rear (without cabin)
- Auto-Throttle (combined accelerator / accelerator pedal)
- Cruise Control
- Rear PTO equipped with headland management system
- Traction control on the rear lift
- Rear towbar
- Weight carrier with 6 frontweights of 17 kg

Code:	Description:				Euro:
SB47H-AG	SB47h Agri tires	F: 8.00-16	R: 12.4-24		19,900,-
SB47H-AG	SB47h Agri tires STAGE V	F: 8.00-16	R: 12.4-24		23,300,-
SB47HC-AG	SB47hc Agri tires	F: 7.00-16	R: 11.2-24		25,900,-
SB47HC-AG	SB47hc Agri tires STAGE V	F: 7.00-16	R: 11.2-24		29,200,-

Additional net price tires:

- TTSB36	Turf tires	F: 27x8.5-15	R: 41x14-20		950,-
- INDSB36H	Industrial tires ROPS	F: 10-16.5	R: 420/70-24		1,600,-
- INDSB36HC	Industrial tires Cabin	F: 25x8.5-14	R: 380/70R19.5		1,400,-
- GALSB36	Galaxy garden pro	F: 260/70R24	R: 380/70R24		1,990,-

Min. outer diameter pro tire type:

- agri tires : 145 cm (narrowest 135 cm)
- agri tires with cabin : 132 cm
- turf tires : 164 cm
- industrial tires : 153 cm
- galaxy garden pro : 151 cm



ACCESSORIES SB36/ SB47

<i>Code:</i>	<i>Description:</i>	<i>Euro:</i>
FRONTLIFT ZUIDBERG		
1404554	Frontlift with double acting hydr. connection in front Cat. 0 or Cat. 1 with catchhooks (w/o cabin only with 13038890)	2,190,-
13038890	Extra hydr. kit (tractor w/o cabin) Mounting lift (net)	1,100,- 290,-
1003753	Front PTO 1000 rpm counterclockwise Mounting PTO (net)	2,690,- 290,-
9002323	Tractor triangle Cat. 0 or Cat. 1	320,-
SHIBAURA FRONTLOADER		
BL15SL	Frontloader with parallel-lifting, bucket 157 cm, Euro-quick-coup. Mounting (net)	4,960,- 305,-
8177-600	Third function frontloader	650,-
42325	Pallet fork 100 cm Euro-quick-coupling	1,100,-
42326	Bale spike	470,-
OTHERS		
42415A	Mudguardset front small with agri tires	370,-
42415B	Mudguardset front width with turf/ industrial tires	370,-
42330	Support for trailer hitchcoupling W255	520,-
42331	Trailer hitchcoupling W255	460,-
42332	Trailer hitchcoupling W255 automatically	650,-
42333	Towing ball coupling W255	440,-
GEVSB36	Air suspension seat	1,500,-
JOYV	Joystick with 2 double acting valves (SB36h/ 47h)	1,600,-
VERL	Extended control handle	150,-



SPECIFICATIONS SHIBAURA SB36 / SB47

MODEL	SB36h(c)		SB47h(c)	
ENGINE (DIESEL)				
Model	A1700N4		A1700T3	
Type	Water cooled 3-cylinder diesel, STAGE V			
Displacement (cc)	1714		1714	
Engine gross power (HP/ kW)	35/ 25.7		45.5/ 33.5	
Torque (Nm)	110.0 @ 1650		145.0 @ 1900	
Rated speed (rpm.)	2600			
Fuel tank capacity (l.)	27			
Combustion system	Indirect			
Battery (V.)	12			
Air cleaner	Dry, element			
TRAVELLING SYSTEM				
Transmission / Groups	Hydrostatic / 3			
Max. forward speed (km/h)	29.2			
Drive system	4 Wheel Drive			
Brake	Wet, multidisc			
Sperddifferential	Rear			
TIRES				
Agri	Front	ROPS: 8-16 / Cabin: 7-16		
	Rear	ROPS: 12.4-24 / Cabin: 11,2 -24		
Turf	Front	27x8.5x15		
	Rear	41x14-20		
Industry	Front	ROPS: 10x16.5 / Cabin: 25x8.5-14		
	Rear	ROPS: 420/70-24 / Cabin: 380/70R19.5		
PTO				
Rear PTO (rpm.)	independent, 540 and 750			
HYDRAULIC SYSTEM				
Main / Steering (lpm.)	33.6 / 18 (180 bar)			
Steering category	Power Assisted Hydrostatic			
Control type	Position / Draft			
Remote Control valve (ROPS / Cabin)	1 double acting rear / 2x double acting rear 1 float position			
Hitch category / Max lifting capacity (kg)	Cat. 1 / 1650			
DIMENSIONS (agri tires)				
Length x Width x Height (ROPS) (mm)	3096 x 1451 x 2643			
Wheelbase (mm)	1671			
Ground clearance (mm)	335			
Weight (ROPS/ Cabin) (kg)	1383 / 1563		1423 / 1563	

SHIBAURA TRACTOR SB62h / SB62hc

FOUR WHEEL DRIVE

ENGINE

4 cylinder, watercooled turbo diesel engine
44.1 kW / 60 hp 2286 cc

TORQUE

195 Nm @ 1700 rpm

TRANSMISSION

Hydrostatic, 3 groups, max. speed 27.3 km/h

REAR PTO

Independent 540 and 750 rpm., headland management, direction of rotation clockwise.

3-POINT LINKAGE

Cat. 2 with lifting capacity 1500 kg

HYDR. CAPACITY

Main 42 liters/ min., steering 19 liters/min., 185 bar

POWER STEERING

Standard

GROUND CLEARANCE

322 mm

FUEL TANK CAPACITY

45 liters

CABIN

SB62hc with factory cabin incl. heating, radio and airconditioning

LENGTH

3282 (with frontweights)

WIDTH

1625

HEIGHT

SB62h: 2489 mm **SB62hc**: 2463 mm

WEIGHT

SB62h: 1722 kg **SB62hc**: 1968 kg

- Clear dashboard and adjustable steering wheel
- Ergonomically placed cross lever for operating 2 dw valves.
- 2 dw valves at the rear, 1 with latch (total of 4 dw valves, 8 connections)
- Auto-Throttle (combined accelerator / accelerator pedal)
- Cruise Control
- Traction control on the rear lift
- Rear towbar
- Hooks on the drawbars
- Weight carrier with 6 frontweights of 17 kg



Code:	Description:	F:	R:	Euro:
SB62H-AG	SB62h Agri-tires	F: 9.5-16	R: 13.6-26	26,600,-
SB62H-AG	SB62h Agri-tires STAGE V	F: 9.5-16	R: 13.6-26	27,900,-
SB62HC-AG	SB62hc Agri-tires	F: 9.5-16	R: 13.6-26	32,400,-
SB62HC-AG	SB62hc Agri-tires STAGE V	F: 9.5-16	R: 13.6-26	33,700,-

Additional net price tires:

- TTSB62	Turf tires	F: 29x12.5-15	R: 44x18-20	1,330,-
- INDSB62	Industrial tires	F: 10-16.5	R: 17.5Lx24	1,330,-
- GALSB62	Galaxy garden pro tires	F: 280/70R16	R: 380/70R24	2,550,-

Min. outer width pro tire type:

- agri tires : 168 cm
- turf tires : 181 cm
- industrial tires : 178 cm



ACCESSORIES SB62

<i>Code:</i>	<i>Description:</i>	<i>Euro:</i>
	FRONTLIFT ZUIDBERG	
1404561	Frontlift SB62	2,200,-
	Mounting lift (net)	290,-
1003933	Front PTO SB62, 1000 rpm counterclockwise	2,760,-
	Mounting PTO (net)	290,-
1303930	Double acting hydraulic connection SB62	190,-
9001194	Tractor triangle	320,-
	SHIBAURA FRONTLOADER	
BL25SL	Frontloader SB62 with parallel-lifting, bucket 157 cm, Euro-coup.	4,960,-
	Mounting (net)	305,-
42325	Pallet fork SB62 100 cm, Euro-quick-coupling	1,100,-
8113-600	Option third function	595,-
	OTHERS SB62	
42284	Mudguardset front	220,-
42285	Mudguardset front adjustable	430,-
42260	Support for trailer hitchcoupling W255	520,-
42331	Trailer hitchcoupling W255	460,-
42332	Trailer hitchcoupling W255 automatically	650,-
42333	Towing ball coupling W255	440,-
42601	Pressure-free return flow	220,-
GEVSB62	Air suspension seat SB62	1.100,-
42262	Air pressure brake system 2 pipes	2.460,-



SHIBAURA TRACTOR SB78mc

FOUR WHEEL DRIVE

ENGINE

4 cylinder, watercooled diesel engine, **STAGE V**

58.1 kW / 78 hp, 3409 cc

TORQUE

295 Nm @ 1250 rpm

TRANSMISSION

SynchroMesh 16 F and 16 R creeper, speed 0.78-32.66 km/h

REAR PTO

Independent 540, 750 and 1000 rpm, headland management, direction of rotation clockwise

3-POINT LINKAGE

Cat. 2 with lifting capacity 1733 kg

HYDR. CAPACITY

Main 50 lpm., steering 30 lpm., 173 bar

POWER STEERING

Standard

GROUND CLEARANCE

488 mm

FUEL TANK CAPACITY

90 liters

CABIN

Factory cabin incl. heating, airconditioning and radio

STANDARD

Weight carrier with 6 frontweights of 20 kg

LENGTH

4117 mm (with frontweights)

WIDTH

1893 mm

HEIGHT

2605 mm

WEIGHT

2835 kg

Code:

SB78MC-AG

Description:

SB78mc agri-tires **STAGE V** F: 11.2-24 R: 16.9-30

Euro:

43,500,-

Additional net price tires:

- GALSB78 Galaxy garden pro tires

F: 380/70R20 R: 480/70R30

3.600,-



ACCESSORIES SB78

<i>Code:</i>	<i>Description:</i>	<i>Euro:</i>
	FRONTLIFT ZUIDBERG	
1410089	Frontlift SB78	2,200,-
	Mounting lift (net)	290,-
1003592	Front PTO SB78, 1000 rpm, counterclockwise	2,995,-
	Mounting PTO (net)	290,-
1303599	Double acting hydraulic connection SB78	190,-
	SHIBAURA FRONTLOADER	
BL45SL	Frontloader SB78 with parallel-lifting, bucket 188 cm, Euro-coup.	6,990,-
	Mounting (net)	305,-
42325	Pallet fork SB78 100 cm Euro-quick-coupling	1.100,-
8142-600	Option third function	650,-
42326	Bale spike	470,-
42385	Manure fork	830,-
	OTHERS SB78	
42315	Support for trailer hitchcoupling W330	830,-
42311	Trailer hitchcoupling W330	500,-
42312	Trailer hitchcoupling W330 automatically	650,-
42261	Towing ball coupling W330	570,-
GEVSB78	Air suspension seat SB78	1,100,-
42380	Air brake system 2 pipes	4.970,-

SPECIFICATIONS SHIBAURA SB62 / SB78

MODEL		SB62h(c)	SB78mc
ENGINE (DIESEL)			
Model		A2300T8	D3400
Type		Water cooled 4-cylinder diesel, STAGE V	
Displacement	(cc)	2286	3409
Engine gross power	(HP/ kW)	60/ 44.1	78/ 58.1
Torque	(Nm/ rpm.)	195.0 @ 1700	295.0 @ 1250
Rated speed	(rpm.)	2600	2500
Fuel tank capacity	(l.)	45	90
Combustion system		Indirect injection	Direct injection
Battery	(V.)	12	
Air cleaner		Dry element	
TRAVELLING SYSTEM			
Transmission / Groups		Hydrostatic / 3	Mechanical / 16 V, 16 A
Forward speed	(km/h.)	0 - 27.3	0.78 - 32.66
Drive system		4 wheel drive	
Clutch		Dry single plate	Wet, multiplate
Brake		Wet, multidisc	
Sperrdifferential		Rear	
TIRES			
Agri	Front	9,5-16	11.2-24
	Rear	13.6-26	16.9-30
Turf	Front	29x12.5-15	
	Rear	44x18-20	
Industry	Front	10x16.5	
	Rear	17.5Lx24	
INDEPENDENT PTO			
Rear PTO	(rpm.)	540 and 750	540, 750 and 1000
HYDRAULIC SYSTEM			
Main / Steering	(lpm.)	42 / 19 (185 bar)	50 / 30 (173 bar)
Steering category		Power Assisted Hydrostatic	
Control type		Position / Draft	
Remote control valve		2x DA rear, 2x DA front	3x DA rear, 2x DA front
Hitch category / max. lift category		(kg) Cat. 2 / 1500	Cat. 2 / 1733
DIMENSIONS (agri-tires)			
L (frontweights) x W x H	(mm)	3282 x 1625 x 2489 (rops)	4117 x 1893 x 2605
Wheelbase	(mm)	1806	2200
Ground clearance	(mm)	322	488
Weight (rops/ cabin)	(kg)	1722 / 1968	2835

SHIBAURA FRONTMOWER CM214

AUTOMATIC FOUR WHEEL DRIVE

When the front wheels are slipping 4%, the four wheel drive is automatically engaged.

ENGINE

3 cylinder, low noise, watercooled Shibaura diesel engine
17.6 kW/ 24 hp (SAE) 16.0 kW/ 21.5 hp (DIN) 1005 cc

TORQUE

59.3 Nm @ 2000 rpm

TRANSMISSION

Hydrostatic: forwards: 0-14 km/h
backwards: 0-8 km/h

TURNING RADIUS

150 cm

PTO

2200 rpm., direction of rotation clockwise

FUEL TANK CAPACITY

28 liters

LxW

213 x 100 cm

HEIGHT

188 cm with rops, 198 cm with cabin

GROUND CLEARANCE

125 mm

TREAD

front: 800 mm rear: 830 mm

WEIGHT with ROPS

530 kg excl. mowerdeck

- Powersteering

- Auto/ full time 4WD can be switch on from the seat

- Safety switch in seat, PTO and brakes

- Weight transfer from mower to tractor

Code:
CM214

Description:
CM214 without mower
with turf tires

F: 20x10.00-8;

R: 16x6.50-8

Euro:
13,980,-



ACCESSORIES SHIBAURA CM214

<i>Code:</i>	<i>Description:</i>	<i>Euro:</i>
SCM48S	SHIBAURA FRONTMOWER 1.22 m side discharge 7 stages cutting height adjustments from 25-115 mm, mower can be lifted up for easy cleaning and maintenance, 120 kg	2,850,-
ST.2002	Mulchset	650,-
4530040	WIEDENMANN mower 1.30 m side discharge	4,970,-
8380040	WIEDENMANN mower 1.30 m rear discharge	5,420,-
1200450	Mulchset	600,-
MUC100-31-1	MÜTHING Flailmower 1.00 m	4,990,-
MUCZ041	Protective shield in mower deck	530,-
KS214	MAUSER CABIN (incl. heating) Mounting (net)	3,950,- 250,-
FKM1250GE	KERSTEN SWEEPER 1.25 x ø 0.37 m	3,200,-
0111	Attachment system necessary for sweeper and frontblade	525,-
1250350	Dust collector with hydr. dump	1,200,-
1250450	Sidebrush ø 0.40 m	660,-
SF1355AO	FRONTBLADE incl. hydr. side adjustment	2,500,-
0111	Attachment system necessary for sweeper and frontblade	525,-
SH016019	Hydr. set with 2 quick coupling (necessary for hydr. side adj.)	820,-



SHIBAURA FRONTMOWER CM254

AUTOMATIC FOUR WHEEL DRIVE

When the front wheels are slipping 4%, the four wheel drive is automatically engaged.

ENGINE

3 cylinder, low noise, watercooled Shibauro diesel, **STAGE V**
17.6 kW/ 23.6 hp / 1496 cc

TORQUE

70.72 Nm @ 1800 rpm.

TRANSMISSION

Hydrost./ 2 groups: forwards: 0-23.6 km/h
backwards: 0-9.6 km/h

BRAKES

Wet discs

PTO

2200 rpm., with stop mechanism when mower is lifted,
direction of rotation counterclockwise

FUEL TANK CAPACITY

51 liters

LxW

2145 x 1365 mm

HEIGHT

1930 mm with ROPS, 2080 mm with cabin

TREAD

front: 990 mm rear: 995 mm

WEIGHT with ROPS

750 kg

- Fast speed
- Powersteering
- Safety switch in seat, PTO and brakes
- Front wheel differential lock
- Speed lock control (Cruise Control)
- Comfortseat with armrests
- Instrument board in adjustable steering column
- Weight transfer from mower to tractor

Code: Description:

CM254 **CM254** without mower with turf tires F: 24x13.00-12 R: 20x8-10 *Euro:* 23,550,-

340003140	Valve kit dual		1.290,-
TBCM314	Terra tires	F: 24x13.00-12 R: 20x8-10 (add. net price)	420,-
W-916.00.290	Lighting set		1,650,-
	Mounting (net)		150,-



ACCESSORIES SHIBAURA CM254

<i>Code:</i>	<i>Description:</i>	<i>Euro:</i>
SCM60S	SHIBAURA FRONTMOWER 1.50 m side discharge, 7 stage cutting height adjustments from 38 to 115 mm, mower can be lifted up 90° for easy cleaning and maintenance, 170 kg	3,750,-
ST.2001	Mulchset 1,50 m	670,-
TMC150F	MORGNIEUX mowerdeck, 1.50 m rear disch. incl. mulchkit	4,990,-
TMC180F	MORGNIEUX mowerdeck, 1.80 m rear disch. incl. mulchkit	5,990,-
8420040	WIEDENMANN MOWER 1.50 m rear discharge	5,730,-
1200451	Mulchset	700,-
8430040	WIEDENMANN MOWER 1.80 m side discharge	6,950,-
8440040	WIEDENMANN MOWER 1.80 m rear discharge	6,950,-
1200452	Mulchset	950,-
MJ61-175	MAJOR mowerdeck synergy 1.62 m	6,590,-
MJ61-200	MAJOR mowerdeck synergy 1.88 m	6,950,-
MJ35-170	MAJOR mowerdeck cyclone 1.70 m	5,690,-
MUFM140-31	MÜTHING Flailmower 1.40 m	5,490,-
MUFM160-31	MÜTHING Flailmower 1.60 m	6,130,-
MUFMZ045	Protective shield in mower deck	660,-
BMF150	MORGNIEUX Flailmower 1.50 m	4,950,-
CMBUMP	REAR WEIGHT bumpershape: ± 100 kg	705,-
KDE	Lift triangle	725,-
BARCABCM314	BARTESKO CABIN Mounting (net)	5,450,- 400,-
BKLIMACM374	Airconditioning	2,890,-
ZLAMP	Flashing light	50,-
	Mounting (net)	30,-
GEVCM	Air suspension seat	1,400,-
378050760	Sun roof	1,800,-

ACCESSORIES SHIBAURA CM254

<i>Code:</i>	<i>Description:</i>	<i>Euro:</i>
PM703	MORGNIEUX GRASSCOLLECTOR with continuously hightipping approx. 2.05 m. and very powerful turbine Mounting (net)	7,990,- 700,-
CLS-H1000	MATEV GRASSCOLLECTOR Grasscollector CLS-H, 1000 litres with hydraulic hightipping approx. 1.90 m Mounting (net)	10,950,- 700,-
1317685	Dismounting frame with wheels	870,-
1317683	Support with hose for SCM60S	770,-
	SWEEPER incl. hydr. side adjustment	
BEZEMCM140	Complete with brush 1.40 x ø 0.42 m	4,400,-
BEZEMCM160	Complete with brush 1.60 x ø 0.42 m	4,600,-
	SNOW BLADE incl. hydr. side adjustment (only with lift triangle KDE)	
PA-4105K	Folding blade incl. plastic scraping rib 1.60 m	1,750,-
BASICL1400	CERRUTTI SNOWBLOWER 1.40 m incl. hydr. adjustment	6,700,-
46020040	WIEDENMANN LEAFBLOWER Whisper Twister	6,900,-
336019133	Tire 20x8-10 per piece	305,-
336035711	Tire 24x13,00-12 per piece	620,-

SPECIFICATIONS SHIBAURA CM214 / CM254

MODEL		CM214	CM254
ENGINE			
Model		S773	N843 STAGE V
Type		Water-cooled, 3-cylinder diesel	
Power	(HP/ kW)	21.5 / 16.0	23.8 / 17.6
Rated speed	(rpm)	2700	2600
Displacement	(cc)	1005	1496
Fuel tank capacity	(l)	28.0	51
Battery	(V-A)	12 - 45	12 - 55
DIMENSIONS			
Length	(mm)	2130	2145
Width	(mm)	1000	1365
Height	(mm)	1875	1935
Ground clearance	(mm)	125	140
Wheel base	(mm)	1050	1250
Tread width front	(mm)	800	940
Tread width rear	(mm)	830	995
Weight incl. ROPS	(kg)	530	750
Tire size front		20x10.00-8	24x13.00-12
Tire size rear		16x6.5-8	20x8.00-10
FRONT PTO			
Type		Belt drive	Wet multi plates
Shaft		ø 25.4 mm/ 21 splines	
Rated speed	(rpm)	2400	2200
SIDE PTO			
Type		Standard	Option
Type		Belt drive	Wet multi plates
Shaft		ø 22.0 mm/ 6 mm	ø 20.0 mm/ 6 mm
Rated speed	(rpm)	2200	2700
TRANSMISSION			
Control		Hydraulic	
Four wheeldrive (mechanical)		Auto 4WD or Full Time 4WD	
Range		1	2
Travelling speed forward	(km/h)	0 - 14.0	0 - 23.6
Travelling speed reverse	(km/h)	0 - 8.0	0 - 9.6
Speed control		2 pedals (forward and reverse)	
Brakes		Wet disc (single pedal control)	

SHIBAURA REEL MOWER SR370

FOUR WHEEL DRIVE ENGINE

3 cylinder, low noise, watercooled Shibaaura diesel engine
19.1 kW / 26.2 HP (SAE) 16.8 kW / 22.8 HP (DIN) 1131 cc
66.0 Nm/ 2200 rpm.

TORQUE TRANSMISSION

Hydrost./ 2 WD: forwards: 0-16 km/h, backwards: 0-6 km/h
4 WD: forwards: 0-8 km/h, backwards: 0-3 km/h

DRIVE CUTTING UNIT

Comfortable hydrostatic operation with 2 groups.
3; diameter 178 mm x width 660 mm; 9-blade (standard),
(option: 7-blade)

CUTTING HEIGHT

10 - 60 mm

CUTTING WIDTH

1800 mm

ROLLER

Front : diameter 80 mm, grooved roller
Rear : diameter 76.3 mm, smooth roller

FUEL TANK CAPACITY

28 liters

LxWxH

2550 x 2030 x 1400 mm

WEIGHT

970 kg

- Powersteering
- Steering column in height and hook adjustable
- Self-cleaning radiator
- Instrument board in steering column
- Backlapping feature

Code:
SR370

Description:
SR370
with turf-tires F: 20x10,00-10 R: 20x10,00-10

Euro:
34,950,-

551166
A72300110
A72300120

Grasscollector (3 pieces) 1,250,-
Front roller scraper per piece 54,-
Rear roller scraper per piece 29,-



SHIBAURA FAIRWAY MOWER SR888

FOUR WHEEL DRIVE

ENGINE

4 cylinder, low noise, watercooled Shibauro diesel engine
33.6 kW / 45 HP, 2216 cc

TRANSMISSION

Hydrost./ 2 groups: forwards: 0-11.8 km/h and 0-17 km/h
backwards: 0-8.3 km/h and 0-11.9 km/h

DRIVE

Automatic four wheel drive or full time four wheel drive
Comfortable hydraulic operation and mechanical driven
for safe working on hills.

CUTTING UNIT

5; diameter 178 mm; 9-blade (standard)
(option: 7-blade and 11-blade)

CUTTING WIDTH

2500 mm

CUTTING HEIGHT

7 - 30 mm

FUEL TANK CAPACITY

43 liters

LENGTH

2750 mm

WIDTH

2870 / 2195 (working / transport)

HEIGHT

2100 mm

WEIGHT

1590 kg

- Powersteering
- Comfortseat with armrests
- Speed lock control
- Mowing and transport speed
- Backlapping feature

Code:
SR888

Description:

SR888

with turf-tires F: 24x12.00-12 R: 20x8.00-10

Euro:
54,900,-

551159
A72310070
A72310060

Grasscollector (5 pieces)

Front roller scraper per piece

Rear roller scraper per piece

1,350,-
54,-
29,-



SPECIFICATIONS SHIBAURA SR370 / SR888

MODEL		SR370EU	SR888
ENGINE			
Model		SHIBAURA S773L	Shibaura N844L
Type		Watercooled 3 cylinder diesel	Water-cooled, 4-cycle, diesel
Power	(HP / kW)	16.8 / 22.8	33.6 / 45
Rated speed	(rpm)	2600	2700
Displacement	(cc)	1131	2216
Fuel tank capacity	(l.)	28,0	43,0
DIMENSIONS			
Length	(mm)	2500	2750
Width (incl. reels)	(mm)	2035	2870
Height (incl. steering wheel)	(mm)	1400	2100 (incl. ROPS)
Weight	(kg)	935	1550
Tire size front		20x10.00-10	24x12.00-12 4PR
Tire size rear		20x10.00-10	20x8.00-10 4PR
TRANSMISSION			
Type & drive		HST/ 4WD	HST/ 4WD
Travelling speed forward	(km/h)	0 - 9.0 / 0 - 18.0	0 - 11.8 / 0 - 17.1
Travelling speed reverse	(km/h)	0 - 4.5 / 0 - 9.0	0 - 8.3 / 0 - 11.9
Forward/ reverse		Dual pedal	
Steering		Hydraulic Power Steering	
Brakes		Pedal Lock	Wet discs
REEL MOWER			
Width of cut	(mm)	1800	2500
Reel Unit Diameter	(mm)	178	178
Reel Unit Width	(mm)	660	560
Number of blades		7-blades (standard)	9-blades (standard)
Front roller	(mm)	ø 80 (grooved)	ø 80
Rear roller	(mm)	ø 76,3 (solid)	ø 76
Height of cut	(mm)	10 ~ 60	7 ~ 30

SHIBAURA ROUGH TERRAIN-/ SLOPEMOWER SG280

FOUR WHEEL DRIVE

ENGINE

3 cylinder, low noise, watercooled Shibaura diesel engine
23.4 kW / 32.2 hp (SAE) 20.6 kW / 28.0 hp (DIN) 1496 cc
92 Nm/ 1800 rpm.

TORQUE

TRANSMISSION

Hydrostatic/ 2 WD: forward: 0-18 km/h, backward: 0-12 km/h
4 WD: forward: 0-9 km/h, backward: 0-6 km/h

TRANSMISSION

Comfortable hydrostatic drive with 2 groups.

FUEL TANK CAPACITY

26 liters

LxWxH

2495 x 1590 x 1730 mm

WEIGHT

770 kg (excl. mowerdeck)

- Powersteering

- Instrument panel

- Seat is horizontal adjustable for comfortable driving on hills

Code:

SG280

Description:

SG280

tires F: 21x11,00-10

R: 21x11,00-10

Euro:

24,900,-

MM62DSGRD

FGM midmounted mower 1.50 m rear discharge

4,550,-

FEU140

FEUCHT longgrass midm. mower 1.40m rear discharge

4,480,-

LAMPFGM

Lighting set

1,660,-



SHIBAURA MOWER WITH COLLECTOR

SX20G/ SX26G/ SX26D



<i>Code:</i>	<i>Description:</i>	<i>Euro:</i>
SX20G	Shibauro SX20G with mid collector Gasoline engine 20 hp, container capacity 410 l., mowerdeck 1.02 m	7,300,-
SX26G-L	Shibauro SX26G lowtipping with mid collector Gasoline engine 26 hp, container capacity 640 l., mowerdeck 1.22 m	15,500,-
SX26G-H	Shibauro SX26G hightipping with mid collector Gasoline engine 26 hp, container capacity 600 l., mowerdeck 1.22 m	16,500,-
SX26D-L	Shibauro SX26D lowtipping with mid collector Engine 20 hp, 3 cylinder diesel, container capacity 640 l., mowerdeck 1.22 m	18,900,-
SX26D-H	Shibauro SX26D hightipping with mid collector Engine 20 hp, 3 cylinder diesel, container capacity 600 l., mowerdeck 1.22 m	19,900,-

ACCESSORIES SX20G / SX26G / SX26D

<i>Code:</i>	<i>Description:</i>	<i>Euro:</i>
Y1050	Cabin	4,320,-
E1181	Heating cabin	1,330,-
Y1102	Led lights cabin rear	120,-
Y1101	Led lights cabin front	190,-
Y0654	Flashing lights	180,-
7602100	Galvanized mowerdeck	270,-
Y0120	Mulchset	260,-
E9621/E1016	Differential lock	910,-
E8767	Electric Frontlift	810,-
Y0007	Towing-hook	130,-
EA236	Frontweight	240,-
E5411/ Y1036	Powerpack	1,230,-
E7781	Snowblade 1.40 m (necessairy E8767 and E5411/Y1036)	830,-
E7844	Sweeper 1.20 m (necessairy E8767 and E5411/Y1036)	2,200,-
F001115	Saltspreader 100 liter (necessairy Y0007)	990,-

MODEL		SX20G	SX26G	SX26D
Engine		Gasoline	Gasoline	Diesel
Power (hp)		20	26 @ 3600 rpm	20 @ 3600 rpm
Fuel tank capacity (l.)		9	20	20
Speed	Forward (km/h)	9	12	12
	Reverse (km/h)	4.5	6	6
Cutting width (mm)		1020	1220	1220
Cutting height (mm)		30 - 100	30 - 130	20 - 120
Caster wheels		4	4	4
Container capacity		410	640	640
Tires	front	15x6.00-6	16x6.5-8	16x6.5-8
	rear	20x10.00-8	23x8.5-12	23x8.5-12
DIMENSIONS				
Length (mm)		2720	2910	2910
Width (mm)		1245	1265	1265
Height (mm)		1150	1280	1280
Weight (kg)		315	565	600

ROTARY MOWERS FOR TRACTOR

<i>Code:</i>	<i>Discharge</i>	<i>Working width</i>	<i>PTO</i>	<i>Euro:</i>
Morgnieux frontmowers				
TMC120AV	Rear	120 cm	2000 rpm.	3,680,-
MMULC12	Mulchkit for	120 cm mower		480,-
TMC150AV	Rear	150 cm	2000 rpm.	4,050,-
MMULC15	Mulchkit for	150 cm mower		450,-
TMC180AV	Rear	180cm	2000 rpm.	4,660,-
MMULC18	Mulchkit for	180 cm mower		530,-
Morgnieux rearmowers				
TMC120AR	Rear	120 cm	540 rpm.	3,680,-
MMULC12	Mulchkit for	120 cm mower		480,-
TMC150AR	Rear	150 cm	540 rpm.	4,050,-
MMULC15	Mulchkit for	150 cm mower		450,-
TMC180AR	Rear	180cm	540 rpm.	4,660,-
MMULC18	Mulchkit for	180 cm mower		530,-
Major Frontmower				
MJ65-150F	Rear	150 cm	1000 rpm.	5,890,-
Major rearmower				
MJ65-150	Rear	150 cm	540 rpm.	4,970,-

FLAIL MOWERS FOR TRACTOR

<i>Code:</i>	<i>Working- width</i>	<i>Knives</i>	<i>max. hp's</i>	<i>Weight</i>	<i>Euro:</i>
Müthing frontmowers					
MUC120-31-1	120 cm	20	25	140 kg	4,790,-
MUC140-31-1	140 cm	24	25	150 kg	4,950,-
MUC160-31-1	160 cm	28	25	160 kg	5,100,-
Müthing rearmowers					
MUC120-31	120 cm	20	35	180 kg	3,420,-
MUC140-31	140 cm	24	35	200 kg	3,650,-
MUC160-31	160 cm	28	35	220 kg	3,990,-
MUCZ041	Protective shield in mower deck				480,-

SALT- AND FERTILIZERSREADER

<i>Code:</i>	<i>Description</i>	<i>Euro:</i>
COSPLS180	COSMO Spreader, PLS180, 180 litres	1,090,-
COSPLS400	COSMO Spreader, PLS400, 300 litres	1,250,-
COSABDP	Cover	90,-
COSBEL	Lighting	180,-



