

# SHIBAURA

## PRICE LIST 2020



- \* Subcompact tractor
- \* Compact tractors
- \* Tractors
- \* Frontmowers
- \* Frontmower with collector
- \* Reelmower
- \* Fairway mower
- \* Mower with collector
- \* Rough terrain-/ slopemower
- \* Accessories



**Shibaura Europe BV**  
Begonialaan 7  
NL - 6851 TE Huissen  
The Netherlands  
T. 0031 26326 9999  
F. 0031 26326 9990  
E. [info@shibaura.com](mailto:info@shibaura.com)  
[www.shibaura.com](http://www.shibaura.com)

## SHIBAURA EUROPE BV

Begonialaan 7  
NL - 6851 TE Huissen  
the Netherlands

Phone 0031 26 326 9999  
Fax 0031 26 326 9990  
Mobile 0031 621883620 (Rob de Dreu)  
0031 629544770 (Wendy Franken)  
0031 621534773 (Fanny Franken)  
0031 654314001 (Paul Franken)

Website : [www.shibaura.com](http://www.shibaura.com)  
E-mail : [info@shibaura.com](mailto:info@shibaura.com)

Chamber of Commerce Arnhem 10036098  
VAT. no. NL009486938B01

Rabobank no. 12.40.42.775  
Swiftcode: RABONL2U  
IBAN: NL92 RABO 0124 0427 75

		<i>Phone:</i>	<i>E-mail:</i>
Sales Benelux	Rob de Dreu	0031 621883620	<a href="mailto:robdedreu@shibaura.com">robdedreu@shibaura.com</a>
Sales/ Spareparts	Hans Broekstra	0031 26 3269991	<a href="mailto:broekstra@shibaura.com">broekstra@shibaura.com</a>
Technical Service	Patrick Janssen	0031 26 3269994	<a href="mailto:td@shibaura.com">td@shibaura.com</a>
Technical Service	Erik Derksen	0031 26 3269994	<a href="mailto:td@shibaura.com">td@shibaura.com</a>
Administration	Angélique Rutten	0031 26 3269996	<a href="mailto:rutten@shibaura.com">rutten@shibaura.com</a>
Managing Director	Fanny Franken	0031 26 3269993	<a href="mailto:fannyfranken@shibaura.com">fannyfranken@shibaura.com</a>
Managing Director	Wendy Franken	0031 26 3269997	<a href="mailto:wendyfranken@shibaura.com">wendyfranken@shibaura.com</a>
Managing Director	Paul Franken	0031 26 3269995	<a href="mailto:franken@shibaura.com">franken@shibaura.com</a>

### Shibaura Deutschland GmbH

Phone/ Fax

Sales Germany  
Sales Germany

Martin Potthoff  
Kai Meschke

Carl-Hans-Straße 4  
0049 2296 999010  
0049 151 72725303  
0049 2296 9990115

D-51674 Wiehl  
0049 2296 9990111  
[potthoff@shibaura.de](mailto:potthoff@shibaura.de)  
[meschke@shibaura.de](mailto:meschke@shibaura.de)

**With this price list all previous price lists are expired.  
All prices are in EURO excl. VAT.  
All deliveries according to Fedecom terms and conditions 2014.**

# CONTENTS:

	<b>PAGE:</b>
SUBCOMPACT TRACTOR SHIBAURA SX25.....	2
COMPACTTRACTOR SHIBAURA SB22m.....	6
COMPACTTRACTOR SHIBAURA SB25h.....	7
COMPACTTRACTOR SHIBAURA SB31m/SB31h.....	8
COMPACTTRACTOR SHIBAURA SB36h/SB36hc.....	11
COMPACTTRACTOR SHIBAURA SB47h/SB47hc.....	12
TRACTOR SHIBAURA SB62h/SB62hc.....	15
TRACTOR SHIBAURA SB78mc.....	16
FRONTMOWER SHIBAURA CM214.....	19
FRONTMOWERS SHIBAURA CM374.....	21
FRONTMOWER WITH COLLECTOR SHIBAURA CM244GC.....	25
REELMOWER SHIBAURA SR370.....	26
FAIRWAY MOWER SHIBAURA SR888.....	27
ROUGH TERRAIN-/ SLOPE MOWER SHIBAURA SG280.....	29
MOWER WITH COLLECTOR SHIBAURA SX20G/ SX26G/ SX26D.....	30
ROTARYMOWERS.....	32
FLAILMOWERS, SALTSPREADERS.....	32

- Prices and technical details are subject to change without previous notice.
- PTO rotation direction mentions the rotation with your face towards the end of the shaft.

# SHIBAURA SUBCOMPACTTRACTOR SX25

## FOUR WHEEL DRIVE

**ENGINE** 3 cylinder, low noise, watercooled diesel engine, **STAGE V**  
21.2 kW / 26.0 hp (SAE) 18.3 kW / 24.5 hp DIN, 1131 cc

**TORQUE** 67.0 Nm/ 2400 rpm.

**TRANSMISSION** Hydrost. / 2 groups: forwards : 0-17 km/h  
backwards : 0-11.2 km/h

**REAR PTO** Independent: rear 540 rpm., mid 2200 rpm.  
direction of rotation clockwise

**3-POINT LINKAGE** Cat. 1 with lifting capacity 715 kg

**HYDR. CAPACITY** 24.6 liters/ min., ≈ 130 bar

**TURNING RADIUS** 254 cm

**TREAD** front: 1164 mm rear: 1270 mm

**GROUND CLEARANCE** 185 mm

**FUEL TANK CAPACITY** 26 liters

**FLOOR** Flat floor without handles

**LENGTH** 244.5 cm

**WIDTH** 118 cm

**HEIGHT** 228 cm

**WEIGHT** with ROB 696 kg

<i>Code:</i>	<i>Description:</i>	<i>Euro:</i>
SX25	<b>SX25</b> (incl. tires as desired)	13,990,-

### *Choice tires:*

- WTT SX26	Wide turf-tires	F: 18x8.5-10	R: 26x12.00-12
- TERRA SX26	Terra/ industrial tires	F: 18x8.5-10	R: 26x12.00-12

### *Additional net price tires, speed about 20 km/h (midmower/ frontloader not possible):*

- INDSX26	Big wide agri tires	F: 23x8,5-12	R: 10,0/75-15,3	650,-
- HSAGRSX26	Big small agri tires	F: 6-12	R: 180/95-16	990,-
- BWTT SX25	Big wide turf tires	F: 27x10,5-15	R: 22x9,5-12	990,-

### **Min. outer diameter pro tire type:**

- turf tires	: 118 cm
- industrial/ terra tires	: 119 cm
- big, wide agri tires	: 118 cm
- big, small agri tires	: 109 cm
- big, wide turf tires	: 119 cm



# ACCESSORIES SHIBAURA SX25

<i>Code:</i>	<i>Description:</i>	<i>Euro:</i>
	<b>SHIBAURA MIDMOUNTED MOWER</b>	
SXM54	Midmounted mower, working width 1.37 m, side discharge	2,800,-
SXM60	Midmounted, working width 1.50 m, side discharge	2,990,-
1317045	Indep. liftkit for midmounted mower (VENT necessary)	520,-
VENT	Valve block	970,-
ST.2003	Mulchset 1.37 m	670,-
ST.2001	Mulchset 1.50 m	670,-
	<b>PAULI FRONTLIFT</b>	
PA-115SH	Frontlift with quick coupling and 2 liftcylinders	1,490,-
PA-120SH	Front PTO, 2000 rpm. (only with PA-115SH)	1,050,-
PA-122SH	Hydraulic set, 2 valves, 4 hydr. connections 2F en 2R	1,050,-
	Mounting (net)	190,-
	Mounting frontlift with big tires (net)	250,-
340003281/60441	Double acting valve with two quick coupling rear	710,-
	Mounting (net)	120,-
	<b>SHIBAURA FRONTLOADER</b> incl. bucket 1.17 m (not with cabin)	
FL26	Frontloader with double acting liftcylinder and hydraulic operation of the bucket	3,690,-
PAL-FL26	Pallet fork	570,-
	Mounting (netto)	250,-
KS322	<b>MAUSER CABIN</b>	5,350,-
	safetyglass, electr. windscreen wiper with sprayer, heating, removable and lockable doors, led-working lights outside mirror, sunblind, height 2,00 m	
	Mounting (net)	350,-
ZLAMP	Flashing light	50,-
	Mounting (net)	30,-
	<b>MATEV GRASSCOLLECTOR</b> (340003281/60441 or PA-122SH necessary)	
1317127	Grasscollector CS-G650, 650 litres	5,490,-
1317129	Grasscollector CS-H650, 650 l. with hydraulic hightipping	6,990,-
1317003	Duo airtyres 260x85 (recommended option)	670,-
1317026	Midmower connection with pipe for midmower	840,-
1317026	Frontmower connection with pipe for frontmower	870,-
	<b>MORGNIEUX GRASSCOLLECTOR</b>	
Turbo530LD	Grasscollector 530LD, 530 litres with manual opening	3,950,-
Turbo530HD	Grasscollector 530HD, 530 litres with hydraulic hightipping	5,650,-
	(340003281/60441 or PA-122SH necessary)	
V04A80	Pair of wheels (recommended)	740,-
V04A82	Road lights	230,-
V04A85	Full container buzzer	230,-

# ACCESSORIES SHIBAURA SX25

<i>Code:</i>	<i>Description:</i>	<i>Euro:</i>
34030040	<b>SNOWBLADE</b> incl. hydr. side adjustment incl. plastic scraping rib 1.40 x 0.50 m	1,990,-
PA-4200K	<b>SNOWBLADE</b> 1.40 m. with lift (short construction) incl. hydr. valve with joystick	3,990,-
<b>MATEV SWEEPER</b>		
1317693	Sweeper 1.40 x Ø 0.45 m incl. hydr. side adjustment	3,990,-
KEHR3	Extra price design with 3 sweeperspeeds	130,-
1317716	Dustcollector	780,-
1317705	Side brush mechanical driven	790,-
1317724	Dustprotector	280,-
<b>CERRUTI SNOWBLOWER</b>		
BASICL1200	Working width 1.20 m, 2000 rpm, incl. side adjustment	6,290,-
<b>OTHER</b>		
PA-129.1SH	Towing-hook rear	660,-
999999004	Frontweight 27 kg (max. 3 pieces) per piece	75,-
STEUNSX	Bracket for mounting frontweight	60,-
Z622.735	Drawbar cat. 1	75,-
HEFBOK	Lift triangle with towing ball	130,-
PA-134.1SH	HST Autopedal	160,-
FARMSL	Air suspension seat	1,030,-
E41W0889	Cruise Control	830,-



# SPECIFICATIONS SHIBAURA SX25

<b>MODEL</b>		<b>SX25</b>
<b>ENGINE (DIESEL)</b>		
Model		S773L-EU
Type		Water cooled, 3-cylinder diesel, <b>STAGE V</b>
Displacement	(cc)	1131
Engine gross power	(DIN HP / kW)	24.5 / 18.3
Torque	(Nm)	67.0 @ 2400
Rated speed	(rpm.)	3000
Fuel tank capacity	(l.)	26
<b>TRAVELLING SYSTEM</b>		
Transmission		HST
Groups		F/R 2
Travelling speed	Forwards	(km/h) 0 - 17.0
	Reverse	(km/h) 0 - 11.5
Differential lock		mechanically switchable
Brake		wet, disc type
<b>TIRES</b>		
Industry	Front	18x8,50-10
	Rear	26x12,00-12
Turf	Front	18x8,50-10
	Rear	26x12,00-12
<b>PTO</b>		
Power	(HP)	20.5
Rear	(rpm.)	540
Mid	(rpm.)	2000
Front		option
<b>HYDRAULIC SYSTEM</b>		
Pump capacity	(lpm/ bar)	24.6/ 130
Steering category		Hydraulic Power Steering
Remote control valve		option: 1 x double acting rear
3-point hitch		Cat. I
Maximum lifting capacity	(kg)	715
<b>DIMENSIONS</b>		
Length	(mm)	2445
Width	(mm)	1180
Height	(mm)	2280
Ground clearance / Wheelbase	(mm)	185 / 1400
Weight	(kg)	696

# SHIBAURA COMPACTTRACTOR SB22m

## FOUR WHEEL DRIVE

### ENGINE

3 cylinder, watercooled diesel engine, **STAGE V**  
15.3 kW / 21 hp, 1058 cc

### TORQUE

61,8 Nm @ 1900 rpm

### TRANSMISSION

Mechanical; 6 F, 2 R, max. speed 19,0 km/h

### REAR PTO

540 and 960 rpm., direction of rotation clockwise

### MID PTO

2600 rpm., direction of rotation clockwise

### 3-POINT LINKAGE

Cat. 1 with lifting capacity 650 kg

### HYDR. CAPACITY

Main 18.2 liters/ min., steering 13 liters/min., 137 bar

### STEERING

Power steering hydraulic

### GROUND CLEARANCE

315 mm

### FUEL TANK CAPACITY

23 liters

### STANDARD

Weight carrier with 6 frontweights of 20 kg

### LENGTH

3066 mm (with frontweights)

### WIDTH agri

1124 mm

### HEIGHT agri

2216 mm

### WEIGHT agri

770 kg

### Code:

SB22M-AG

### Description:

**SB22m** Agri tires

F: 6.00-12

R:9.5-16

### Euro:

11,950,-

### Additional net price tires:

- TTSB22

Turf tires

F: 23-8.5-12

R: 33x12.5-16.5

700,-

- INDSB22

Industrial tires

F: 23-8.5-12

R: 12-16.5

700,-

### Min. outer diameter pro tire type:

- agri tires : 112 cm

- turf tires : 133 cm

- industrial tires : 132 cm





# SHIBAURA COMPACTTRACTOR SB25h

## FOUR WHEEL DRIVE ENGINE

3 cylinder, watercooled diesel engine, **STAGE V**  
17.9 kW / 24 hp, 1175 cc

## TORQUE

75.6 Nm @ 2000 rpm

## TRANSMISSION

Hydrostatic; 2 groups, max. speed 21.4 km/h

## REAR PTO

540 and 960 rpm., direction of rotation clockwise

## MID PTO

2600 rpm., direction of rotation clockwise

## 3-POINT LINKAGE

Cat. 1 with lifting capacity 650 kg

## HYDR. CAPACITY

Main 18.2 liters/ min., steering 13 liters/min., 137 bar

## POWER STEERING

Standard

## GROUND CLEARANCE

315 mm

## FUEL TANK CAPACITY

23 liters

## STANDARD

Weight carrier with 6 frontweights of 20 kg

## LENGTH

3066 mm (with frontweights)

## WIDTH agri

1124 mm

## HEIGHT agri

2216 mm

## WEIGHT agri

780 kg

### Code:

SB25H-AG

### Description:

**SB25h** Agri tires

F: 6.00-12

R:9.5-16

### Euro:

13,550,-

### Additional net price tires:

- TTSB22

Turf tires

F: 23x8.5-12

R: 33x12.5-16.5

700,-

- INDSB22

Industrial tires

F: 23x8.5-12

R: 12-16.5

700,-

### Min. outer diameter pro tire type:

- agri tires : 112 cm

- turf tires : 133 cm

- industrial tires : 132 cm



# SHIBAURA COMPACTTRACTOR SB31m / SB31h

## FOUR WHEEL DRIVE

### ENGINE

3 cylinder, watercooled diesel engine

23.2 kW / 30 hp 1175 cc

### TORQUE

86,5 Nm @ 2000 rpm

### TRANSMISSION

**SB31m:** Mechanical, 6 F and 2 R, max. speed 21.9 km/h

**SB31h:** Hydrostatic, 2 groups, max. speed 24.6 km/h

### REAR PTO

540 and 960 rpm., direction of rotation clockwise

### MID PTO

2600 rpm., direction of rotation clockwise

### 3-POINT LINKAGE

Cat. 1 with lifting capacity 650 kg

### HYDR. CAPACITY

Main 18.2 liters/ min., steering 13 liters/min., 137 bar

### POWER STEERING

Standard

### GROUND CLEARANCE

407 mm

### FUEL TANK CAPACITY

23 liters

### STANDARD

Weight carrier with 6 frontweights of 20 kg

### LENGTH

3122 mm (with frontweights)

### WIDTH agri

1369 mm

### HEIGHT agri

2330 mm

### WEIGHT agri

**SB31m:** 885 kg    **SB31h:** 908 kg

### Code:

### Description:

### Euro:

SB31M-AG	<b>SB31m</b>	Agri tires	F: 7-16	R: 11.2-20	14,900,-
SB31H-AG	<b>SB31h</b>	Agri tires	F: 7-16	R: 11.2-20	15,950,-

### Additional net price tires:

- TTSB22	Turf tires	F: 23x8.5-12	R: 33x12.5-16.5	700,-
- INDSB22	Industrial tires	F: 23x8.5-12	R: 12-16.5	700,-

### Min. outer diameter pro tire type:

- agri tires : 127 cm
- turf tires : 133 cm
- industrial tires : 138 cm



# ACCESSORIES SB22/ SB25/ SB31

<i>Code:</i>	<i>Description:</i>	<i>Euro:</i>
BM60	<b>SHIBAURA MIDMOUNTED MOWER</b> Midmounted mower, working width 1,50 m	2,980,-
<b>PAULI FRONTLIFT</b>		
PA-3100B	Frontlift with quick coupling Cat. 0	1,490,-
PA-3105B	Front PTO, 2000 rpm, clockwise (only with PA-3100B)	1,380,-
PA-3106B	Hydraulic set, 2 valves, 4 hydr. connections 2 F and 2 lift Mounting (net)	1,250,- 290,-
<b>SHIBAURA FRONTLOADER</b>		
BL00SL	Frontloader SB 22/ 25 incl. bucket 121 cm (not with cabin)	3,950,-
42120/42221	Pallet fork 100 cm, pin-coupling Mounting (net)	1,040,- 305,-
BL05SL	Frontloader SB31 parallel-lifting, bucket 138 cm, Euro-coupling	4,530,-
42325	Pallet fork 100 cm, Euro-quick coupling	1,100,-
42224	Third function Mounting (net)	755,- 305,-
<b>CABIN</b>		
42180	Cabin SB22/ 25 with heating, height 198 cm	5,490,-
42185	Cabin SB31 with heating, height 211 cm Mounting (net)	5,490,- 390,-
<b>OTHERS</b>		
42111	Mudguardset front SB22/ 25 with agri tires	190,-
42112	Mudguardset front SB22/ 25 with turf/ industrial tires	190,-
42113	Mudguardset front SB31 with agri tires	190,-
42162	Support for trailer hitchcoupling W180	700,-
42163	Adjustable trailer hitchcoupling W180 (only with 42162)	420,-
42164	Towing ball coupling W180	400,-
42160	Hitchcoupling (attached to top link)	460,-



# SPECIFICATIONS SHIBAURA SB22 / SB25 / SB31

MODEL		SB22m	SB25h	SB31m	SB31h
<b>ENGINE (DIESEL)</b>					
Model		A1000N2	A1100N2	A1100T2	
Type		Water cooled 3-cylinder diesel			
Displacement (cc)		1058	1175		
Engine gross power (HP/ kW)		21 / 15.3	24 / 17.9	30 / 23.2	30 / 23.2
Torque (Nm)		61.8 @ 1900	75.6 @ 2000	86.5 @ 2000	
Rated speed (rpm.)		2600			
Fuel tank capacity (l.)		23			
Air cleaner		Dry, element			
<b>TRAVELLING SYSTEM</b>					
Transmission		Mechanical	Hydrostatic	Mechanical	Hydrostatic
Groups		6 F / 2 R	2	6 F / 2 R	2
Max forward speed		19	21.4	21,9	24,6
Drive system		4 wheel drive			
Clutch / Brake		Dry, single plate / Wet multidisc			
Sperrdifferential		Rear			
<b>TIRES</b>					
Agri	Front	6-12	6-12	7-16	7-16
	Rear	9.5-16	9.5-16	11.2-20	11.2-20
Turf	Front	23x8.5x12	23x8.5x12	23x8.5x12	23x8.5x12
	Rear	33x12.5-16.5	33x12.5-16.5	33x12.5-16.5	33x12.5-16.5
Industry	Front	23x8.5x12	23x8.5x12	23x8.5x12	23x8.5x12
	Rear	12-16.5	12-16.5	12-16.5	12-16.5
<b>PTO</b>					
Rear PTO (rpm.)		540 and 960			
Mid PTO (rpm.)		2600			
<b>HYDRAULIC SYSTEM</b>					
Main (lpm./ bar)		18.2/ 137			
Steering (lpm.)		13			
Steering category		Power Assisted Hydrostatic			
Control type		Position			
Remote control valve		2 double acting rear			
Hitch category/ max. lift capacity (kg)		Cat. 1/ 650			
<b>DIMENSIONS (agri tires)</b>					
Length x Width x Height (mm)		3066 x 1124 x 2216		3122 x 1369 x 2330	
Wheelbase/ ground clearance (mm)		1502/ 315		1670/ 407	
Weight incl. ROPS (kg)		770	780	885	908

# SHIBAURA COMPACTTRACTOR SB36h / SB36hc

## FOUR WHEEL DRIVE

### ENGINE

3 cylinder, watercooled diesel engine  
25.7 kW / 35 hp, 1714 cc

### TORQUE

110 Nm @ 1650 rpm

### TRANSMISSION

Hydrostatic, 3 groups, max. speed 29.2 km/h

### REAR PTO

Independent 560 and 780 rpm.,  
direction of rotation clockwise

### 3-POINT LINKAGE

Cat. 1 with lifting capacity 1650 kg

### HYDR. CAPACITY

Main 33.6 liters/ min., steering 18 liters/min., 180 bar

### POWER STEERING

Standard

### GROUND CLEARANCE

335 mm

### FUEL TANK CAPACITY

27 liters

### CABIN

**SB36hc** with factory cabin incl. heating, air conditioning,  
radio and led-working lights front and rear

### LxWxH rops/ agri

3096 x 1451 x 2643 mm

### WEIGHT

**SB36h**: 1427 kg

- Clear dashboard and adjustable steering wheel
- Ergonomically placed cross lever for operating 2 dw valves.
- 2 dw valves at the rear, 1 with latch (cabin)
- 1 dw valve rear (without cabin)
- Auto-Throttle (combined accelerator / accelerator pedal)
- Cruise Control
- Rear PTO equipped with headland management system
- Traction control on the rear lift
- Rear towbar
- Weight carrier with 6 frontweights of 17 kg

### Code:

### Description:

### Euro:

SB36H-AG	<b>SB36h</b> Agri tires	F: 8-16	R: 12.4-24	17,950,-
SB36HC-AG	<b>SB36hc</b> Agri tires	F: 7-16	R: 11.2-24	23,900,-

### Additional net price tires:

- TTSB36	Turf tires	F: 27x8.5-15	R: 41x14-20	900,-
- INDSB36H	Industrial tires	F: 10-16.5	R: 420/70-24	900,-
- INDSB36HC	Industrial tires cabin	F: 25x8.5-14	R: 380/70R19.5	900,-
- GALSB36	Galaxy garden pro	F: 260/70R16	R: 380/70R24	1,990,-

### Min. outer diameter pro tire type:

- agri tires	: 149 cm
- agri tires with cabin	: 149 cm
- turf tires	: 164 cm
- industrial tires	: 153 cm
- galaxy garden pro	: 151 cm



# SHIBAURA COMPACTTRACTOR SB47h / SB47hc

## FOUR WHEEL DRIVE

### ENGINE

3 cylinder, watercooled diesel engine

33.5 kW / 45.5 hp 1714 cc

### TORQUE

145 Nm @ 1900 rpm

### TRANSMISSION

Hydrostatic, 3 groups, max. speed 29.2 km/h

### REAR PTO

Independent 560 and 780 rpm.,

direction of rotation clockwise

### 3-POINT LINKAGE

Cat. 1 with lifting capacity 1650 kg

### HYDR. CAPACITY

Main 33.6 liters/ min., steering 18 liters/min., 180 bar

### POWER STEERING

Standard

### GROUND CLEARANCE

335 mm

### FUEL TANK CAPACITY

27 liters

### CABIN

**SB47hc** with factory cabin incl. heating, air conditioning,

radio and led-workinglights front and rear

### LxWxH

rops/ agri

3096 x 1451 x 2643 mm

### WEIGHT

agri

**SB47h**: 1427 kg

- Clear dashboard and adjustable steering wheel
- Ergonomically placed cross lever for operating 2 dw valves.
- 2 dw valves at the rear, 1 with latch (cabin)
- 1 dw valve rear (without cabin)
- Auto-Throttle (combined accelerator / accelerator pedal)
- Cruise Control
- Rear PTO equipped with headland management system
- Traction control on the rear lift
- Rear towbar
- Weight carrier with 6 frontweights of 17 kg

### Code:

### Description:

### Euro:

SB47H-AG	<b>SB47h</b> Agri tires	F: 8.00-16	R: 12.4-24	19,900,-
SB47HC-AG	<b>SB47hc</b> Agri tires	F: 7.00-16	R: 11.2-24	25,900,-

### Additional net price tires:

- TTSB36	Turf tires	F: 27x8.5-15	R: 41x14-20	900,-
- INDSB36H	Industrial tires ROPS	F: 10-16.5	R: 420/70-24	900,-
- INDSB36HC	Industrial tires Cabin	F: 25x8.5-14	R: 380/70R19.5	900,-
- GALSB36	Galaxy garden pro	F: 260/70R24	R: 380/70R24	1,990,-

### Min. outer diameter pro tire type:

- agri tires : 149 cm
- agri tires with cabin : 149 cm
- turf tires : 164 cm
- industrial tires : 153 cm
- galaxy garden pro : 151 cm



# ACCESSORIES SB36/ SB47

<i>Code:</i>	<i>Description:</i>	<i>Euro:</i>
<b>FRONTLIFT ZUIDBERG</b>		
1404554	Frontlift with double acting hydr. connection in front Cat. 0 or Cat. 1 with catchhooks (w/o cabin only with 13038890)	2,190,-
13038890	Extra hydr. kit (tractor w/o cabin) Mounting lift (net)	1,100,- 290,-
1003753	Front PTO 1000 rpm counterclockwise Mounting PTO (net)	2,690,- 290,-
9002323	Tractor triangle Cat. 0 or Cat. 1	320,-
<b>SHIBAURA FRONTLOADER</b>		
BL15SL	Frontloader with parallel-lifting, bucket 157 cm, Euro-quick-coup. Mounting (net)	4,960,- 305,-
42224	Third function frontloader	760,-
42325	Pallet fork 100 cm Euro-quick-coupling	1,100,-
<b>OTHERS</b>		
42415A	Mudguardset front small with agri tires	370,-
42415B	Mudguardset front width with turf/ industrial tires	370,-
42300	Support for trailer hitchcoupling W255	520,-
42331	Trailer hitchcoupling W255	460,-
42332	Trailer hitchcoupling W255 automatically	650,-
42333	Towing ball coupling W255	440,-
GEVSB36	Air suspension seat	1,500,-
JOYV	Joystick with 2 double acting valves (SB36h/ 47h)	1,600,-
VERL	Extended control handle	150,-



# SPECIFICATIONS SHIBAURA SB36 / SB47

MODEL	SB36h	SB47h
<b>ENGINE (DIESEL)</b>		
Model	A1700N4	A1700T3
Type	Water cooled 3-cylinder diesel	
Displacement (cc)	1714	1714
Engine gross power (HP/ kW)	35/ 25.7	45.5/ 33.5
Torque (Nm)	110.0 @ 1650	145.0 @ 1900
Rated speed (rpm.)	2600	
Fuel tank capacity (l.)	27	
Combustion system	Indirect	
Battery (V.)	12	
Air cleaner	Dry, element	
<b>TRAVELLING SYSTEM</b>		
Transmission / Groups	Hydrostatic / 3	
Max. forward speed (km/h)	29.2	
Drive system	4 Wheel Drive	
Brake	Wet, multidisc	
Sperddifferential	Rear	
<b>TIRES</b>		
Agri	Front	ROPS: 8-16 / Cabin: 7-16
	Rear	ROPS: 12.4-24 / Cabin: 11,2 -24
Turf	Front	27x8.5x15
	Rear	41x14-20
Industry	Front	ROPS: 10x16.5 / Cabin: 25x8.5-14
	Rear	ROPS: 420/70-24 / Cabin: 380/70R19.5
<b>PTO</b>		
Rear PTO (rpm.)	independent, 560 and 780	
<b>HYDRAULIC SYSTEM</b>		
Main / Steering (lpm.)	33.6 / 18 (180 bar)	
Steering category	Power Assisted Hydrostatic	
Control type	Position / Draft	
Remote Control valve	1 double acting rear / 2x double acting rear 1 float position	
Hitch category / Max lifting capacity (kg)	Cat. 1 / 1650	
<b>DIMENSIONS (agri tires)</b>		
Length x Width x Height (mm)	3096 x 1451 x 2643	
Wheelbase (mm)	1671	
Ground clearance (mm)	335	
Weight incl. ROPS (kg)	1427	



# SHIBAURA TRACTOR SB62h / SB62hc

## FOUR WHEEL DRIVE

### ENGINE

4 cylinder, watercooled turbo diesel engine  
44.1 kW / 60 hp 2286 cc

### TORQUE

195 Nm @ 1700 rpm

### TRANSMISSION

Hydrostatic, 3 groups, max. speed 27.3 km/h

### REAR PTO

Independent 584 and 791 rpm., headland management, direction of rotation clockwise.

### 3-POINT LINKAGE

Cat. 2 with lifting capacity 1500 kg

### HYDR. CAPACITY

Main 42 liters/ min., steering 19 liters/min., 185 bar

### POWER STEERING

Standard

### GROUND CLEARANCE

322 mm

### FUEL TANK CAPACITY

45 liters

### CABIN

**SB62hc** with factory cabin incl. heating, radio and airconditioning

### LENGTH

3288 (with frontweights)

### WIDTH

1625

### HEIGHT

**SB62h**: 2489 mm    **SB62hc**: 2463 mm

### WEIGHT

**SB62h**: 1722 kg    **SB62hc**: 1968 kg

- Clear dashboard and adjustable steering wheel
- Ergonomically placed cross lever for operating 2 dw valves.
- 2 dw valves at the rear, 1 with latch (total of 4 dw valves, 8 connections)
- Auto-Throttle (combined accelerator / accelerator pedal)
- Cruise Control
- Traction control on the rear lift
- Rear towbar
- Hooks on the drawbars
- Weight carrier with 6 frontweights of 17 kg

<i>Code:</i>	<i>Description:</i>			<i>Euro:</i>
SB62H-AG	<b>SB62h</b> Agri-tires	F: 9.5-16	R: 13.6-26	26,600,-
SB62HC-AG	<b>SB62hc</b> Agri-tires	F: 9.5-16	R: 13.6-26	32,400,-

### *Additional net price tires:*

- TTSB62	Turf tires	F: 29x12.5-15	R: 44x18-20	1,330,-
- INDSB62	Industrial tires	F: 10-16.5	R: 17.5Lx24	1,330,-

### **Min. outer width pro tire type:**

- agri tires : 168 cm
- turf tires : 181 cm
- industrial tires : 178 cm



# SHIBAURA TRACTOR SB78mc

## FOUR WHEEL DRIVE

### ENGINE

4 cylinder, watercooled diesel engine

58.1 kW / 78 hp, 3409 cc

### TORQUE

295 Nm @ 1250 rpm

### TRANSMISSION

SynchroMesh 16 F and 16 R creeper, speed 0.78-32.66 km/h

### REAR PTO

Independent 540, 750 and 1000 rpm.,  
direction of rotation clockwise

### 3-POINT LINKAGE

Cat. 2 with lifting capacity 1733 kg

### HYDR. CAPACITY

Main 50 lpm., steering 30 lpm., 173 bar

### POWER STEERING

Standard

### GROUND CLEARANCE

488 mm

### FUEL TANK CAPACITY

90 liters

### CABIN

Factory cabin incl. heating, airconditioning and radio

### STANDARD

Weight carrier with 6 frontweights of 20 kg

### LENGTH

4117 mm (with frontweights)

### WIDTH

1893 mm

### HEIGHT

2605 mm

### WEIGHT

2765 kg

### Code:

SB78MC-AG

### Description:

**SB78mc** Agri-tires

F: 11.2-24

R: 16.9-30

### Euro:

39,950,-



# ACCESSORIES SB62/ SB78

<i>Code:</i>	<i>Description:</i>	<i>Euro:</i>
	<b>FRONTLIFT ZUIDBERG</b>	
1404561	Frontlift SB62	2,200,-
	Mounting lift (net)	290,-
1003933	Front PTO SB62, 1000 rpm counterclockwise	2,760,-
	Mounting PTO (net)	290,-
1303930	Double acting hydraulic connection SB62	190,-
9001194	Tractor triangle	320,-
1410089	Frontlift SB78	2,200,-
	Mounting lift (net)	290,-
1003592	Front PTO SB78, 1000 rpm, counterclockwise	2,995,-
	Mounting PTO (net)	290,-
1303599	Double acting hydraulic connection SB78	190,-
	<b>SHIBAURA FRONTLOADER</b>	
BL25SL	Frontloader SB62 with parallel-lifting, bucket 157 cm, Euro-coup.	4,960,-
42325	Pallet fork SB62 100 cm, Euro-quick-coupling	1,100,-
BL45SL	Frontloader SB78 with parallel-lifting, bucket 188 cm, Euro-coup.	6,990,-
42325	Pallet fork SB78 100 cm Euro-quick-coupling	1,100,-
	Mounting (net)	305,-
	<b>OTHERS SB62</b>	
42284	Mudguardset front	220,-
42285	Mudguardset front adjustable	430,-
42260	Support for trailer hitchcoupling W255	520,-
42331	Trailer hitchcoupling W255	460,-
42332	Trailer hitchcoupling W255 automatically	650,-
42333	Towing ball coupling W255	440,-
42601	Pressure-free return flow	220,-
GEVSB62	Air suspension seat SB62	1,100,-
	<b>OTHERS SB78</b>	
42318	Mudguardset front	400,-
42315	Support for trailer hitchcoupling W330	560,-
42311	Trailer hitchcoupling W330	460,-
42312	Trailer hitchcoupling W330 automatically	650,-
42261	Towing ball coupling W330	570,-
GEVSB78	Air suspension seat SB78	1,100,-

# SPECIFICATIONS SHIBAURA SB62 / SB78

MODEL		SB62h(c)	SB78mc
<b>ENGINE (DIESEL)</b>			
Model		A2300T8	D3400
Type		Water cooled 4-cylinder diesel	
Displacement	(cc)	2286	3409
Engine gross power	(HP/ kW)	60/ 44.1	78/ 58.1
Torque	(Nm/ rpm.)	195.0 @ 1700	295.0 @ 1250
Rated speed	(rpm.)	2600	2500
Fuel tank capacity	(l.)	45	90
Combustion system		Indirect injection	Direct injection
Battery	(V.)	12	
Air cleaner		Dry element	
<b>TRAVELLING SYSTEM</b>			
Transmission / Groups		Hydrostatic / 3	Mechanical / 16 V, 16 A
Forward speed	(km/h.)	0 - 27.3	0.78 - 32.66
Drive system		4 wheel drive	
Clutch		Dry single plate	Wet, multiplate
Brake		Wet, multidisc	
Sperdifferential		Rear	
<b>TIRES</b>			
Agri	Front	9,5-16	11.2-24
	Rear	13.6-26	16.9-30
Turf	Front	29x12.5-15	
	Rear	44x18-20	
Industry	Front	10x16.5	
	Rear	17.5Lx24	
<b>INDEPENDENT PTO</b>			
Rear PTO	(rpm.)	584 and 791	540, 750 and 1000
<b>HYDRAULIC SYSTEM</b>			
Main / Steering	(lpm.)	42 / 19 (185 bar)	50 / 30 (173 bar)
Steering category		Power Assisted Hydrostatic	
Control type		Position / Draft	
Remote control valve		2x DA rear, 2x DA front	3x DA rear, 2x DA front
Hitch category / max. lift category		(kg) Cat. 2 / 1500	Cat. 2 / 1733
<b>DIMENSIONS (agri-tires)</b>			
L (frontweights) x W x H	(mm)	3282 x 1625 x 2489 (rops)	4117 x 1893 x 2605
Wheelbase	(mm)	1806	2200
Ground clearance	(mm)	322	488
Weight (rops/ cabin)	(kg)	1722 / 1968	2765

# SHIBAURA FRONTMOWER CM214

## AUTOMATIC FOUR WHEEL DRIVE

When the front wheels are slipping 4%, the four wheel drive is automatically engaged.

## ENGINE

3 cylinder, low noise, watercooled Shibaura diesel engine  
17.6 kW/ 24 hp (SAE) 16.0 kW/ 21.5 hp (DIN) 1005 cc

## TORQUE

59.3 Nm @ 2000 rpm

## TRANSMISSION

Hydrostatic: forwards: 0-14 km/h  
backwards: 0-8 km/h

## TURNING RADIUS

150 cm

## PTO

2200 rpm., direction of rotation clockwise

## FUEL TANK CAPACITY

28 liters

## LxW

213 x 100 cm

## HEIGHT

188 cm with rops, 198 cm with cabin

## GROUND CLEARANCE

125 mm

## TREAD

front: 800 mm rear: 830 mm

## WEIGHT with ROPS

530 kg excl. mowerdeck

- Powersteering

- Auto/ full time 4WD can be switch on from the seat

- Safety switch in seat, PTO and brakes

- Weight transfer from mower to tractor

*Code:*  
CM214

*Description:*  
**CM214 without mower**  
with turf tires

F: 20x10.00-8;

R: 16x6.50-8

*Euro:*  
13,980,-



# ACCESSORIES SHIBAURA CM214

<i>Code:</i>	<i>Description:</i>	<i>Euro:</i>
SCM48S	<b>SHIBAURA FRONTMOWER</b> 1.22 m side discharge 7 stages cutting height adjustments from 25-115 mm, mower can be lifted up for easy cleaning and maintenance, 120 kg	2,850,-
ST.2002	Mulchset	650,-
8380040 1200450	<b>WIEDENMANN</b> mower 1.30 m rear discharge Mulchset	5,420,- 600,-
MUC100-31-1 MUCZ041	<b>MÜTHING</b> Flailmower 1.00 m Protective shield in mower deck	4,990,- 530,-
KS214	<b>MAUSER CABIN</b> (incl. heating) Mounting (net)	3,950,- 250,-
FKM1250GE 0111	<b>KERSTEN SWEEPER</b> 1.25 x ø 0.37 m Attachment system necessary for sweeper and frontblade	3,200,- 525,-
1250350	Dust collector with hydr. dump	1,200,-
1250450	Sidebrush ø 0.40 m	660,-
SF1355AO 0111	<b>FRONTBLADE</b> incl. hydr. side adjustment Attachment system necessary for sweeper and frontblade	2,500,- 525,-
SH016019	<b>Hydr. set</b> with 2 quick coupling (necessary for hydr. side adj.)	820,-



# SHIBAURA FRONTMOWER CM374

## AUTOMATIC FOUR WHEEL DRIVE

When the front wheels are slipping 4%, the four wheel drive is automatically engaged.

## ENGINE

3 cylinder, low noise, watercooled Shibaura diesel engine  
29.4 kW/ 40 hp (SAE) 26.8 kW/ 36 hp (DIN) 1662 cc

## TORQUE

103.1 Nm @ 1700 rpm.

## TRANSMISSION

Hydrost./ 2 groups: forwards: 0-10 km/h and 0-25 km/h  
backwards: 0-7 km/h and 0-16 km/h

## TURNING CIRCLE

120 cm

## BRAKES

Wet discs

## PTO

2200 rpm., with stop mechanism when mower is lifted,  
direction of rotation counterclockwise

## FUEL TANK CAPACITY

50.5 liters

## LxW

215 x 137 cm

## HEIGHT

193 cm with ROPS, 208 cm with cabin

## GROUND CLEARANCE

150 mm

## TREAD

front: 990 mm rear: 995 mm

## WEIGHT with ROPS

770 kg

- Fast speed 25 km/h.
- Powersteering
- Safety switch in seat, PTO and brakes
- Front wheel differential lock
- Speed lock control
- Comfortseat with armrests
- Instrument board in adjustable steering column
- Auto/ full time 4WD can be switch from the seat
- Weight transfer from mower to tractor

Code: Description:

CM374 **CM374** without mower with turf tires F: 24x13.00-12 R: 20x8-10 Euro: 21,500,-

TBCM314 Terra tires F: 24x13.00-12 R: 20x8-10 (add. net price) 420,-

W-916.00.290 Lighting set 1,590,-

Mounting (net) 150,-



# ACCESSORIES SHIBAURA CM374

<i>Code:</i>	<i>Description:</i>	<i>Euro:</i>
SCM60S	<b>SHIBAURA FRONTMOWER</b> 1.50 m side discharge, 7 stage cutting height adjustments from 38 to 115 mm, mower can be lifted up 90° for easy cleaning and maintenance, 170 kg	3,750,-
ST.2001	Mulchset 1,50 m	670,-
TMC150F	<b>MORGNIEUX</b> mowerdeck, 1.50 m rear disch. incl. mulchkit	4,990,-
TMC180F	<b>MORGNIEUX</b> mowerdeck, 1.80 m rear disch. incl. mulchkit	5,990,-
8420040	<b>WIEDENMANN MOWER</b> 1.50 m rear discharge	5,730,-
1200451	Mulchset	700,-
8430040	<b>WIEDENMANN MOWER</b> 1.80 m side discharge	6,950,-
8440040	<b>WIEDENMANN MOWER</b> 1.80 m rear discharge	6,950,-
1200452	Mulchset	950,-
MJ61-175	<b>MAJOR</b> mowerdeck synergy 1.62 m	6,590,-
MJ61-200	<b>MAJOR</b> mowerdeck synergy 1.88 m	6,950,-
MJ35-170	<b>MAJOR</b> mowerdeck cyclone 1.70 m	5,690,-
MUFM140-31	<b>MÜTHING</b> Flailmower 1.40 m	5,490,-
MUFM160-31	<b>MÜTHING</b> Flailmower 1.60 m	6,130,-
MUFMZ045	Protective shield in mower deck	660,-
BMF150	<b>MORGNIEUX</b> Flailmower 1.50 m	4,950,-
CMBUMP	<b>REAR WEIGHT</b> bumpershape: ± 100 kg	705,-
KDE	Lift triangle	725,-
BARCABCM314	<b>BARTESKO CABIN</b> Mounting (net)	5,450,- 400,-
BKLIMACM374	Airconditioning	2,890,-
ZLAMP	Flashing light	50,-
	Mounting (net)	30,-
GEVCM	Air suspension seat	1,400,-
378050760	Sun roof	1,800,-





# ACCESSORIES SHIBAURA CM374

<i>Code:</i>	<i>Description:</i>	<i>Euro:</i>
	<b>MORGNIEUX GRASSCOLLECTOR</b>	
PM703	with continuously hightipping approx. 2.05 m. and very powerful turbine Mounting (net)	7,990,- 700,-
	<b>MATEV GRASSCOLLECTOR</b>	
CLS-H1000	Grasscollector CLS-H, 1000 litres with hydraulic hightipping approx. 1.90 m Mounting (net)	10,950,- 700,-
1317685	Dismounting frame with wheels	870,-
1317683	Support with hose for SCM60S Mounting (net)	770,- 700,-
	<b>SWEEPER</b> incl. hydr. side adjustment	
BEZEMCM	Complete with brush 1.50 x ø 0.42 m	4,400,-
023529	Dust collector 1.50 m	790,-
023506	Side brush ø 0.52 m, driven by V-belt	640,-
	<b>SNOW BLADE</b> incl. hydr. side adjustment (only with lift triangle KDE)	
PA-4105K	Folding blade incl. plastic scraping rib 1.60 m	1,750,-
BASICL1400	<b>CERRUTTI SNOWBLOWER</b> 1.40 m incl. hydr. adjustment	6,700,-
46020040	<b>WIEDENMANN LEAFBLOWER</b> Whisper Twister	6,900,-
336019133	Tire 20x8-10 per piece	305,-
336035711	Tire 24x13,00-12 per piece	620,-



# SPECIFICATIONS SHIBAURA CM214 / CM374

MODEL		CM214	CM374
<b>ENGINE</b>			
Model		S773	N843-L
Type		Water-cooled, 3-cylinder diesel	
Power	(HP/ kW)	21.5 / 16.0	36.0 / 26.8
Rated speed	(rpm)	2700	2700
Displacement	(cc)	1005	1662
Fuel tank capacity	(l)	28.0	50.5
Battery	(V-A)	12 - 45	12 - 55
<b>DIMENSIONS</b>			
Length	(mm)	2130	2415
Width	(mm)	1000	1370
Height	(mm)	1875	1930
Ground clearance	(mm)	125	140
Wheel base	(mm)	1050	1250
Tread width front	(mm)	800	940
Tread width rear	(mm)	830	995
Weight incl. ROPS	(kg)	530	770
Tire size front		20x10.00-8	24x13.00-12
Tire size rear		16x6.5-8	20x8.00-10
<b>FRONT PTO</b>			
Type		Belt drive	Wet multi plates
Shaft		ø 25.4 mm/ 21 splines	
Rated speed	(rpm)	2400	2200
<b>SIDE PTO</b>			
Type		Standard	Option
Type		Belt drive	Wet multi plates
Shaft		ø 22.0 mm/ 6 mm	ø 20.0 mm/ 6 mm
Rated speed	(rpm)	2200	2700
<b>TRANSMISSION</b>			
Control		Hydraulic	
Four wheeldrive (mechanical)		Auto 4WD or Full Time 4WD	
Range		1	2
Travelling speed forward	(km/h)	0 - 14.0	0 - 10.0 0 - 24.5
Travelling speed reverse	(km/h)	0 - 8.0	0 - 17.1
Speed control		2 pedals (forward and reverse)	
Brakes		Wet disc (single pedal control)	

# SHIBAURA FRONTMOWER / COLLECTOR CM244GC

## AUTOMATIC FOUR WHEEL DRIVE

### ENGINE

3 cylinder, watercooled diesel engine  
20 kW/ 27 hp (SAE) 18 kW/ 24 hp (DIN) 1123 cc

### TRANSMISSION

Hydrostat: forwards: 0-15 km/h  
backwards: 0-10 km/h

### BRAKES

Drum brakes

### CAPACITY CONTAINER

550 liters

### PTO

2000 rpm.

### FUEL TANK CAPACITY

30 liters

### LxWxH

2330 x 1195 x 1450 mm

### GROUND CLEARANCE

125 mm

### WEIGHT

680 kg

- Blow cut grass into 550 litres capacity grasscollector hopper
- Hydraulic high dump collection hopper with lifting height of 190 cm
- All controls, pedals and levers are placed in suitable position to contribute efficient work
- Full hydraulic drive with continuously 2-pedal-steering
- Mechanical drive of wheels, mower deck and turbine
- Cruise control
- Four wheel drive allows for enhanced traction on hilly ground
- Easily entrance for daily maintenance

### Code:

CM244GC

### Description:

**CM244GC** with mower 1.37 m  
with tires F: 20x10.00-8 R: 210/60 D8

### Euro:

26,400,-

### STVZOCM244

Lighting set  
Mounting (net)

1,590,-

150,-



# SHIBAURA REEL MOWER SR370

## FOUR WHEEL DRIVE

### ENGINE

3 cylinder, low noise, watercooled Shibauro diesel engine  
19.1 kW / 26.2 HP (SAE) 16.8 kW / 22.8 HP (DIN) 1131 cc  
66.0 Nm/ 2200 rpm.

### TORQUE

### TRANSMISSION

Hydrost./ 2 WD: forwards: 0-16 km/h, backwards: 0-6 km/h  
4 WD: forwards: 0-8 km/h, backwards: 0-3 km/h

### DRIVE

### CUTTING UNIT

Comfortable hydrostatic operation with 2 groups.  
3: diameter 178 mm x width 660 mm; 9-blade (standard),  
(option: 7-blade)

### CUTTING HEIGHT

10 - 60 mm

### CUTTING WIDTH

1800 mm

### ROLLER

Front : diameter 80 mm, grooved roller  
Rear : diameter 76.3 mm, smooth roller

### FUEL TANK CAPACITY

28 liters

### LxWxH

2550 x 2030 x 1400 mm

### WEIGHT

970 kg

### - Powersteering

### - Steering column in height and hook adjustable

### - Self-cleaning radiator

### - Instrument board in steering column

### - Backlapping feature

### Code:

SR370

### Description:

**SR370**

with turf-tires F: 20x10,00-10 R: 20x10,00-10

### Euro:

34,950,-

551166

A72300110

A72300120

**Grasscollector** (3 pieces)

**Front roller scraper** per piece

**Rear roller scraper** per piece

1,250,-

54,-

29,-



# SHIBAURA FAIRWAY MOWER SR888

## FOUR WHEEL DRIVE

### ENGINE

4 cylinder, low noise, watercooled Shibauro diesel engine  
33.6 kW / 45 HP, 2216 cc

### TRANSMISSION

Hydrost./ 2 groups: forwards: 0-11.8 km/h and 0-17 km/h  
backwards: 0-8.3 km/h and 0-11.9 km/h

### DRIVE

Automatic four wheel drive or full time four wheel drive  
Comfortable hydraulic operation and mechanical driven  
for safe working on hills.

### CUTTING UNIT

5; diameter 178 mm; 9-blade (standard)  
(option: 7-blade and 11-blade)

### CUTTING WIDTH

2500 mm

### CUTTING HEIGHT

7 - 30 mm

### FUEL TANK CAPACITY

43 liters

### LENGTH

2750 mm

### WIDTH

2870 / 2195 (working / transport)

### HEIGHT

2100 mm

### WEIGHT

1590 kg

- Powersteering

- Comfortseat with armrests

- Speed lock control

- Mowing and transport speed

- Backlapping feature

*Code:*

SR888

*Description:*

**SR888**

with turf-tires F: 24x12.00-12 R: 20x8.00-10

*Euro:*

54,900,-

551159

A72310070

A72310060

**Grasscollector** (5 pieces)

**Front roller scraper** per piece

**Rear roller scraper** per piece

1,350,-

54,-

29,-



# SPECIFICATIONS SHIBAURA SR370 / SR888

MODEL		SR370EU	SR888
<b>ENGINE</b>			
Model		SHIBAURA S773L	Shibaura N844L
Type		Watercooled 3 cylinder diesel	Water-cooled, 4-cycle, diesel
Power	(HP / kW)	16.8 / 22.8	33.6 / 45
Rated speed	(rpm)	2600	2700
Displacement	(cc)	1131	2216
Fuel tank capacity	(l.)	28,0	43,0
<b>DIMENSIONS</b>			
Length	(mm)	2500	2750
Width (incl. reels)	(mm)	2035	2870
Height (incl. steering wheel)	(mm)	1400	2100 (incl. ROPS)
Weight	(kg)	935	1550
Tire size front		20x10.00-10	24x12.00-12 4PR
Tire size rear		20x10.00-10	20x8.00-10 4PR
<b>TRANSMISSION</b>			
Type & drive		HST/ 4WD	HST/ 4WD
Travelling speed forward	(km/h)	0 - 9.0 / 0 - 18.0	0 - 11.8 / 0 - 17.1
Travelling speed reverse	(km/h)	0 - 4.5 / 0 - 9.0	0 - 8.3 / 0 - 11.9
Forward/ reverse		Dual pedal	
Steering		Hydraulic Power Steering	
Brakes		Pedal Lock	Wet discs
<b>REEL MOWER</b>			
Width of cut	(mm)	1800	2500
Reel Unit Diameter	(mm)	178	178
Reel Unit Width	(mm)	660	560
Number of blades		7-blades (standard)	9-blades (standard)
Front roller	(mm)	ø 80 (grooved)	ø 80
Rear roller	(mm)	ø 76,3 (solid)	ø 76
Height of cut	(mm)	10 ~ 60	7 ~ 30

# SHIBAURA ROUGH TERRAIN-/ SLOPEMOWER SG280

## FOUR WHEEL DRIVE

### ENGINE

3 cylinder, low noise, watercooled Shibaura diesel engine  
23.4 kW / 32.2 hp (SAE) 20.6 kW / 28.0 hp (DIN) 1496 cc  
92 Nm/ 1800 rpm.

### TORQUE

### TRANSMISSION

Hydrostatic/ 2 WD: forward: 0-18 km/h, backward: 0-12 km/h  
4 WD: forward: 0-9 km/h, backward: 0-6 km/h

### TRANSMISSION

Comfortable hydrostatic drive with 2 groups.

### FUEL TANK CAPACITY

26 liters

### LxWxH

2495 x 1590 x 1730 mm

### WEIGHT

770 kg (excl. mowerdeck)

- Powersteering

- Instrument panel

- Seat is horizontal adjustable for comfortable driving on hills

*Code:*

SG280

*Description:*

**SG280**

tires F: 21x11,00-10

R: 21x11,00-10

*Euro:*

24,900,-

MM62DSGRD

**FGM** midmounted mower 1.50 m rear discharge

4,550,-

FEU140

**FEUCHT** longgrass midm. mower 1.40m rear discharge

4,480,-

LAMPFGM

Lighting set

1,660,-



# SHIBAURA MOWER WITH COLLECTOR

## SX20G/ SX26G/ SX26D



<i>Code:</i>	<i>Description:</i>	<i>Euro:</i>
SX20G	<b>Shibaura SX20G</b> with mid collector Gasoline engine 20 hp, container capacity 410 l., mowerdeck 1.02 m	7,300,-
SX26G-L	<b>Shibaura SX26G</b> lowtipping with mid collector Gasoline engine 26 hp, container capacity 640 l., mowerdeck 1.22 m	15,500,-
SX26G-H	<b>Shibaura SX26G</b> hightipping with mid collector Gasoline engine 26 hp, container capacity 600 l., mowerdeck 1.22 m	16,500,-
SX26D-L	<b>Shibaura SX26D</b> lowtipping with mid collector Engine 20 hp, 3 cylinder diesel, container capacity 640 l., mowerdeck 1.22 m	18,900,-
SX26D-H	<b>Shibaura SX26D</b> hightipping with mid collector Engine 20 hp, 3 cylinder diesel, container capacity 600 l., mowerdeck 1.22 m	19,900,-



# ACCESSORIES SX20G / SX26G / SX26D

<i>Code:</i>	<i>Description:</i>	<i>Euro:</i>
Y1050	Cabin	4,320,-
E1181	Heating cabin	1,330,-
Y1102	Led lights cabin rear	120,-
Y1101	Led lights cabin front	190,-
Y0654	Flashing lights	180,-
7602100	Galvanized mowerdeck	270,-
Y0120	Mulchset	260,-
E9621/E1016	Differential lock	910,-
E8767	Electric Frontlift	810,-
Y0007	Towing-hook	130,-
EA236	Frontweight	240,-
E5411/ Y1036	Powerpack	1,230,-
E7781	Snowblade 1.40 m (necessairy E8767 and E5411/Y1036)	830,-
E7844	Sweeper 1.20 m (necessairy E8767 and E5411/Y1036)	2,200,-
F001115	Saltspreader 100 liter (necessairy Y0007)	990,-

MODEL		SX20G	SX26G	SX26D
Engine		Gasoline	Gasoline	Diesel
Power (hp)		20	26 @ 3600 rpm	20 @ 3600 rpm
Fuel tank capacity (l.)		9	20	20
Speed	Forward (km/h)	9	12	12
	Reverse (km/h)	4.5	6	6
Cutting width (mm)		1020	1220	1220
Cutting height (mm)		30 - 100	30 - 130	20 - 120
Caster wheels		4	4	4
Container capacity		410	640	640
Tires	front	15x6.00-6	16x6.5-8	16x6.5-8
	rear	20x10.00-8	23x8.5-12	23x8.5-12
<b>DIMENSIONS</b>				
Length (mm)		2720	2910	2910
Width (mm)		1245	1265	1265
Height (mm)		1150	1280	1280
Weight (kg)		315	565	600

## ROTARY MOWERS FOR TRACTOR

<i>Code:</i>	<i>Discharge</i>	<i>Working width</i>	<i>PTO</i>	<i>Euro:</i>
<b>Morgnieux frontmowers</b>				
TMC120AV	Rear	120 cm	2000 rpm.	3,680,-
MMULC12	Mulchkit for	120 cm mower		480,-
TMC150AV	Rear	150 cm	2000 rpm.	4,050,-
MMULC15	Mulchkit for	150 cm mower		450,-
TMC180AV	Rear	180cm	2000 rpm.	4,660,-
MMULC18	Mulchkit for	180 cm mower		530,-
<b>Morgnieux rearmowers</b>				
TMC120AR	Rear	120 cm	540 rpm.	3,680,-
MMULC12	Mulchkit for	120 cm mower		480,-
TMC150AR	Rear	150 cm	540 rpm.	4,050,-
MMULC15	Mulchkit for	150 cm mower		450,-
TMC180AR	Rear	180cm	540 rpm.	4,660,-
MMULC18	Mulchkit for	180 cm mower		530,-
<b>Major Frontmower</b>				
MJ65-150F	Rear	150 cm	1000 rpm.	5,890,-
<b>Major rearmower</b>				
MJ65-150	Rear	150 cm	540 rpm.	4,970,-

## FLAIL MOWERS FOR TRACTOR

<i>Code:</i>	<i>Working- width</i>	<i>Knives</i>	<i>max. hp's</i>	<i>Weight</i>	<i>Euro:</i>
<b>Müthing frontmowers</b>					
MUC120-31-1	120 cm	20	25	140 kg	4,790,-
MUC140-31-1	140 cm	24	25	150 kg	4,950,-
MUC160-31-1	160 cm	28	25	160 kg	5,100,-
<b>Müthing rearmowers</b>					
MUC120-31	120 cm	20	35	180 kg	3,420,-
MUC140-31	140 cm	24	35	200 kg	3,650,-
MUC160-31	160 cm	28	35	220 kg	3,990,-
MUCZ041	Protective shield in mower deck				480,-

## SALT- AND FERTILIZERSREADER

<i>Code:</i>	<i>Description</i>	<i>Euro:</i>
COSPLS180	<b>COSMO</b> Spreader, PLS180, 180 litres	990,-
COSPLS400	<b>COSMO</b> Spreader, PLS400, 300 litres	1,190,-
COSABDP	Cover	90,-
COSBEL	Lighting	180,-





