

Specifications*

MODEL		SB62h	SB78mc
ENGINE (DIESEL)			
Model		A2300T8	D3400
Type		Water cooled 4-cylinder diesel	
Displacement	(cc)	2286	3409
Engine gross power	(HP/ kW)	60/ 44.1	78/ 58.1
Rated speed	(rpm.)	2600	2500
Fuel tank capacity	(l.)	45	90
Combustion system		Indirect injection	Directe injection
Battery	(V.)	12	
Air cleaner		Dry element	
TRAVELLING SYSTEM			
Transmission		Hydrostatic	Mechanical
Groups		3	16 V, 16 A (creeper)
Max. forward speed	(km/h.)	27.3	39.85
Drive system		4 wheel drive	
Clutch		Dry single plate	Wet, multiplate
Brake		Wet, multidisc	
Sperrdifferential		Rear	
TIRES			
Agri	Front	9.5-16	11.2-24
	Rear	13.6-26	16.9-30
Turf	Front	29x12.5-15	
	Rear	44x18-20	
Industry	Front	10x16.5	
	Rear	17.5Lx24	
PTO			
Rear PTO	(rpm.)	independent: 584 and 791	independent: 540, 750 and 1000
HYDRAULIC SYSTEM			
Main	(lpm.)	42	50
Steering	(lpm.)	19	30
Steering category		Power Assisted Hydrostatic	
Control type		Position / Draft	
Remote control valve		2x double acting rear, 2x double acting front	3x double acting rear, 2x double acting front
Hitch category		Cat. 2	
Max. lift capacity	(kg)	1733	1500
DIMENSIONS			
Length (with frontweights)	(mm)	3282	4117
Width	(mm)	1625	1893
Height	(mm)	2489	2605
Min. turning radius	(mm)	4750	7400
Ground clearance	(mm)	322	488
Wheelbase	(mm)	1806	2200
Weight incl. ROPS	(kg)	1722	2765

*The specifications are subject to change without notice.



Important information

• Improper use of any product may cause serious or fatal injury. Read, understand and follow carefully the operating and safety instructions in your owner's manual before using such products.



SHIBAURA EUROPE BV

Begonialaan 7

NL - 6851 TE Huissen

T. 0031 (0)26 326 9999

F. 0031 (0)26 326 9990

E. info@shibaura.com

I. www.shibaura.com

Dealer: