

## Options

Roof and protective net



Grascollector



Scrapers



### Important information

- Improper use of any product may cause serious or fatal injury. Read, understand and follow carefully the operating and safety instructions in your owner's manual before using such products.

# SHIBAURA

SHIBAURA EUROPE BV

Begonialaan 7

NL - 6851 TE Huissen

T. (0031) 026 326 9999

F. (0031) 026 326 9990

E. info@shibaura.com

I. www.shibaura.com

Dealer:

## Specifications\*

MODEL		SR888
<b>DIMENSIONS</b>		
Length	(mm)	2750
Width	mowing (mm)	2870
	transport (mm)	2195
Height	(mm)	2100 (incl. ROPS)
Wheel base	(mm)	1595
Tread width	front (mm)	1735
	rear (mm)	1150
Ground clearance	(mm)	160
Tires	front	24x12.00-12 4PR
	rear	20x8.00-10 4PR
Weight	(kg)	1550
<b>ENGINE</b>		
Model	Shibaura N844L	
Type	water-cooled, 4-cycle, diesel	
Number of cylinders	4	
Displacement	(cc)	2216
Power	(DIN kW (hp))	33.6 (45)
Rated speed	(rpm)	2700
Fuel tank capacity	(l)	43
Battery	75D26L	
<b>TRANSMISSION</b>		
Type	hydrostatic, 2 range high/ low, autom. 4WD or permanent 4WD	
Brake	wet disc	
Steering	hydraulic power steering	
Travelling range	forward	2
	reverse	2
Travelling speed	forward (km/h)	L: 0 ~ 11.8 H: 0 ~ 17.1
	reverse (km/h)	L: 0 ~ 8.3 H: 0 ~ 11.9
<b>FAIRWAY MOWER</b>		
Total width of cut	(mm)	2500
Reel width	(mm)	560
Reel diameter	(mm)	Ø 178
Number of reel	9-blades (standard), 7/ 11-blades (option)	
Height of cut	(mm)	7 ~ 30

\* We reserve the right to discontinue models or change specifications without notice.