

MAJOR SPECIFICATIONS

ITEM		SX26
Engine		
Model		S773L-EU
Number of cylinders		3
Total displacement		cc 1,131
Bore and stroke		mm(in) 77×81(3.0×3.2)
Engine gross power		HP(kw) 26.0 (19.4)
P.T.O power		HP(kw) 20.5 (15.3)
Rated revolution		rpm 3,000
Capacities		
Fuel tank		ℓ (U.S gal) 25.5 (6.75)
Transmission oil		ℓ (U.S gal) 13.0 (3.4)
Front axle oil		ℓ (U.S gal) 2.0 (0.5)
Drive train		
Clutch		—
Transmission	Shuttle	Infinite
	Main	HST
	Range	2 range (High/Low)
	Speeds	—
Ground speed(Tire for industrial) km/h (mp/h)	Forward 3,000rpm	0-16.6 (0-10.3)
	Reverse 3,000rpm	0-11.2 (0-7.0)
4-wheel drive		Mechanical
Quick turn(QT)		None
Brake		Wet disk type
Differential lock		Standard for rear axle
Tires		
Agricultural	Front	—
	Rear	—
Industrial	Front	18×8.5-8 R4
	Rear	26×12.00-12 R4
Turf	Front	18×8.5-8 R3
	Rear	26×12.00-12 R3
Hydraulic system		
Pump capacity		ℓ /min(gpm) 24.6 (6.5)
Steering		Hydraulic Power Steering
3-point hitch		SAE Category I
Max. lifting capacity kg(lbs.)	61cm(24in) Behind	318 (700)
	Lower link end	715 (1,580)
P.T.O		
Rear	Type	Independent
	P.T.O shaft	1-3/8" 6 splines
	Speed (P.T.O rpm/engine rpm)	540/3,000
Mid	P.T.O shaft()★	16/32" 15 splines
	Speed (P.T.O rpm@engine rpm)	2,200@3,020
Min. turning radius		m(feet) 2.54 (8.33)
Weight (with ROPS)		kg(lbs) 700 (1,543)

(★) In compliance with A.S.A.E. standards

※We reserve the right to discontinue models or change specifications without notice.