

Specifications *

Model		CM214	CM314	CM374
Engine				
Model		S773	N843	N843-L
Type		Water-cooled, 3-cylinder diesel		
Gross horsepower	(SAE hp (kw)) / (DIN hp (kW))	24 (17.6) / 21.5 (16.0)	33.9 (25.5) / 30.0 (22.4)	40 (29.4) / 36.0 (26.8)
Rated speed	(rpm)	2700	2700	2700
Displacement	(cc)	1005	1496	1662
Fuel tank capacity	(l)	28,0	50,5	
Batterie	(V-A)	12 - 45	12 - 55	
Dimensions				
Overall length	(mm)	2130	2415	
Overall width	(mm)	1000	1370	
Overall height	(mm)	1875	1930	
Ground clearance	(mm)	125	140	
Wheel base	(mm)	1050	1250	
Tread width front	(mm)	800	940	
Tread width rear	(mm)	830	995	
Weight incl. ROPS	(kg)	530	755	770
Tire size front		20x10.00-8	24x13.00-12	
Tire size rear		16x6.5-8	20x8.00-10	
Front PTO				
Type		Belt drive	Wet multi plates	
Shaft		ø 25.4 mm/ 21 splines		
Rated speed	(rpm)	2400	2200	
Side PTO				
		Standard	Option	
Type		Belt drive	Wet multi plates	
Shaft		ø 22.0 mm/ 6 mm	ø 20.0 mm/ 6 mm	
Rated speed	(rpm)	2200	2700	
Transmission				
Control		Hydraulic		
Four wheel drive (mechanical)		Auto 4WD or Full Time 4WD	Auto 4WD or Full Time 4WD incl. differential lock	
Range		1	2	
Travelling speed forward	(km/h)	0 - 14.0	0 - 10.0	0 - 24.5
Travelling speed reverse	(km/h)	0 - 8.0	0 - 17.1	
Speed control		2 pedals (forward and reverse)		
Brakes		Wet disc (single pedal control)		
Control/ safety system				
Mower lifting		Hydraulic		
Steering		Hydraulic		
ROPS		Standard		
Parking brake		Standard		
Seatbelt		Standard		
Automatic engine stop feature		Standard		
Safety engine starting switch		Standard		
Shibaura mower (option)				
Type	(mm)	120	150 or 180	
Cutting height	(mm)	25 - 115	38 - 115	38 - 115
Cutting width	(mm)	1220	1520	1830
Weight	(kg)	120	175	204

Important information

• Improper use of any product may cause serious or fatal injury. Read, understand and follow carefully the operating and safety instructions in your owner's manual before using such products.

* Specifications and design subject to change without notice.



SHIBAURA EUROPE BV
 Begonialaan 7
 NL - 6851 TE Huissen
 Tel. (0031) 026 326 9999
 Fax (0031) 026 326 9990
 E-mail: info@shibaura.com
 www.shibaura.com

Dealer: