

# SPECIFICATIONS

<b>Model</b>		<b>SR370EU</b>
<b>Engine</b>		
Model		SHIBAURA S773L
Type		watercooled 3 cylinder diesel
Horsepower (SAE hp (kw)) / (DIN hp (kW))		16.8 (29.4) / 16.8 (22.8)
Rated speed (rpm)		2600
Displacement (cc)		1130
Fuel tank capacity (l)		28
<b>Dimensions</b>		
Overall length (mm)		2500
Overall width (incl. reels) (mm)		2035
Overall height (incl. a steering) (mm)		1400
Weight (kg)		935
Tire size front		20 x 10.00-10
Tire size rear		20 x 10.00-10
<b>Transmission</b>		
Type & Drive		HST/ 2WD & 4WD switchable
Travelling speed forward (km/h)		0 - 9.0 / 0 - 18.0
Travelling speed reverse (km/h)		0 - 4.5 / 0 - 9.0
Shift Control		Dual Pedal
Steering		Hydraulic Power Steering
Parking brake		Pedal Lock
<b>Reel Mower</b>		
Total width of cut (mm)		1800
Reel Unit Diameter (mm)		178
Reel Unit Width (mm)		660
Number of blades		7 Blade-standard
Front Roller (mm)		ø 80 (grooved)
Rear Roller (mm)		ø 76.3 (solid)
Height of Cut (mm)		10 ~ 60
Option		Canopy / Protective Net/ Grass Catcher

We reserve the right to discontinue models or change specifications without notice.